


Bohren mit Wendeplatten





APPLICATION GUIDE & INDEX

Holder	Type	Application	Size Range	Page No	Insert	Page No.
QXF 3xD		 	Ø13mm - Ø50mm	126-127	 SPMX	135
QXF 4xD		 	Ø16mm - Ø33mm	128-129		
QXF 5xD		 	Ø13mm - Ø40mm	130-131		
CXF 2.5xD		 	Ø51mm - Ø117mm	132		
HXF		 	Ø70mm - Ø160mm	133	 WCMX	136
IXF 3xD		 	Ø10mm - Ø33mm	138	 IX10 - IX32	141-146
IXF 5xD		 	Ø10mm - Ø33mm	139		
IXF 8xD		 	Ø10mm - Ø33mm	140		
SPADE SS ST/FLUTE STUB		 	Ø9.5mm - Ø35mm	148	 SERIES Y - 2	161-176
SPADE SS ST/FLUTE SHORT		 	Ø9.5mm - Ø65mm	149	 SERIES Y - 4	



APPLICATION GUIDE & INDEX

Holder	Type	Application	Size Range	Page No	Insert	Page No.
SPADE SS SP/FLUTE INTERMEDIATE		 	Ø18mm - Ø47mm	150	 SERIES 1 - 3	161-176
SPADE SS SP/FLUTE STANDARD		 	Ø9.5mm - Ø65mm	151	 SERIES Y - 4	
SPADE SS SP/FLUTE EXTENDED		 	Ø9.5mm - Ø35mm	152	 SERIES Y - 2	
SPADE SS ST/FLUTE EXTENDED		 	Ø35.7mm - Ø65mm	153	 SERIES 3 - 4	
SPADE MTS ST/FLUTE SHORT		 	Ø9.5mm - Ø114mm	154	 SERIES Y - 8	
SPADE MTS SP/FLUTE INTERMEDIATE		 	Ø18mm - Ø47mm	155	 SERIES 1 - 3	
SPADE MTS SP/FLUTE STANDARD		 	Ø9.5mm - Ø114mm	156	 SERIES Y - 8	
SPADE MTS SP/FLUTE EXTENDED		 	Ø9.5mm - Ø35mm	157	 SERIES Y - 2	
SPADE MTS ST/FLUTE EXTENDED		 	Ø35.7mm - Ø114mm	158	 SERIES 3 - 8	
SPADE DRILL ACCESSORIES						159

INSERT GRADE GUIDE

		P STEEL				M STAINLESS STEEL				K CAST IRON			
		05	15	25	35	05	15	25	35	05	15	25	35
PVD	ET602			602				602				602	
	ET30P			30P								30P	
		HARDER ← → TOUGHER				HARDER ← → TOUGHER				HARDER ← → TOUGHER			
		N NON-FERROUS				S HRSA				H HARDENED STEEL			
		05	15	25	35	05	15	25	35	05	15	25	35
PVD	ET602			602				602				602	
	ET30P												
		HARDER ← → TOUGHER				HARDER ← → TOUGHER				HARDER ← → TOUGHER			

P20 - P35 **ET602**
M20 - M40
K20 - K35
N05 - N35
S15 - S25
H20 - H40

Ultra dense PVD coating optimised for drilling applications, suitable for most materials

PVD - TiAlN

P20 - P40 **ET30P**
K20 - K40

Multi layer PVD coating optimised for thermal resistance and higher shear strength

PVD - TiSiN

SPMX EDGE PREPARATION GUIDE

P	M	K	N	S	H	Edge Preparation Guide		
●	○	●	○	○	○		Standard Edge Preparation	General machining, first choice
○	●	○	○	●	○		MS	Sharp geometry for Stainless Steel and HRSA



SPADE INSERT TYPES

	4F POINT Four facet point, for high stability and hole straightness with less thrust force. Ideal choice for all steels.		FLAT BOTTOM For holes requiring flat bottom and drilling on sloping or inclined surface.
	STANDARD POINT For drilling in a wide range of materials.		

SPADE DRILL INSERT GUIDE

	CARBIDE P40A 4F POINT, TiAlN COATED Four facet point, for high stability and hole straightness with less thrust force. Ideal choice for all steels.		HSS T15A 4F POINT, TiAlN COATED Four facet point, for high stability and hole straightness with less thrust force. Ideal choice for all steels and nickel alloys.
	CARBIDE K10A TiAlN COATED High performance in cast iron drilling over 220 HB.		HSS T15A TiAlN COATED Ideal choice for tool steels and softer nickel alloys
	CARBIDE K10T TiN COATED High performance in malleable cast iron.		HSS T15T TiN COATED For carbon steels and alloy steels.
	CARBIDE K20A TiAlN COATED For stainless steel and high temperature alloys. Also suitable for cast iron.		HSS M4A TiAlN COATED For carbon steel, alloy steel, stainless steel and cast iron.
	CARBIDE K20T TiN COATED Excellent performance in aluminium and cast iron.		HSS M4T TiN COATED For carbon steel, cast iron and aluminium.
	CARBIDE P40A TiAlN COATED For carbon steel and high alloy steel.		HSS M48A TiAlN COATED For tool steel, hard cast iron and high temperature alloys.
	CARBIDE P40T TiN COATED For long tool life in low carbon steel.		HSS M48T TiN COATED For carbon steel and softer nickel alloys.
			HSS T15A FLAT BOTTOM, TiAlN COATED For holes requiring flat bottom and drilling on sloping or inclined surface.

INDEXABLE DRILLING
4 CORNER INSERT





UNIMASTER QX

Insert Type	
	SPMX 0502.. SPMX 0602.. SPMX 07T3.. SPMX 0904.. SPMX 1104.. SPMX 1405..

EDP Code	TOOL CODE	DC	DMM	BD	LS	LU	LF	OAL	Insert	Screw	Wrench
QXF3D1300	QXF3D1300	13.0	20	25	50	39	57	107	SPMX 05	TXS2043	TXW05
QXF3D1400	QXF3D1400	14.0				42	60	110			
QXF3D1500	QXF3D1500	15.0				45	63	113			
QXF3D1600	QXF3D1600	16.0	25	32	56	48	69	125	SPMX 06	TXS2205	TXW07
QXF3D1650	QXF3D1650	16.5				49.5	70.5	126.5			
QXF3D1700	QXF3D1700	17.0				51	72	128			
QXF3D1750	QXF3D1750	17.5				52.5	73.5	129.5			
QXF3D1800	QXF3D1800	18.0				54	75	131			
QXF3D1850	QXF3D1850	18.5				55.5	76.5	132.5			
QXF3D1900	QXF3D1900	19.0				57	78	134			
QXF3D1950	QXF3D1950	19.5				58.5	79.5	135.5			
QXF3D2000	QXF3D2000	20.0				60	82	138			
QXF3D2050	QXF3D2050	20.5				61.5	83.5	139.5			
QXF3D2100	QXF3D2100	21.0				63	85	141			
QXF3D2150	QXF3D2150	21.5				64.5	86.5	142.5			
QXF3D2200	QXF3D2200	22.0	32	45	60	66	96	156	SPMX 07	TXS2507	TXW08
QXF3D2250	QXF3D2250	22.5				67.5	97.5	157.5			
QXF3D2300	QXF3D2300	23.0				69	99	159			
QXF3D2350	QXF3D2350	23.5				70.5	100.5	160.5			
QXF3D2400	QXF3D2400	24.0				72	102	162			
QXF3D2450	QXF3D2450	24.5				73.5	103.5	163.5			
QXF3D2500	QXF3D2500	25.0				75	105	165			
QXF3D2550	QXF3D2550	25.5				76.5	106.5	166.5			
QXF3D2600	QXF3D2600	26.0				78	108	168			
QXF3D2650	QXF3D2650	26.5				79.5	109.5	169.5			
QXF3D2700	QXF3D2700	27.0				81	111	171			
QXF3D2750	QXF3D2750	27.5				82.5	112.5	172.5			

► ABS and Plain shanks available to order

INDEXABLE DRILLING
4 CORNER INSERT



UNIMASTER QX



Insert Type	
	SPMX 0502.. SPMX 0602.. SPMX 07T3.. SPMX 0904.. SPMX 1104.. SPMX 1405..

EDP Code	TOOL CODE	DC	DMM	BD	LS	LU	LF	OAL	Insert	Screw	Wrench
QXF3D2800	QXF3D2800	28.0	32	45	60	84	114	174	SPMX 09	TXS3509	TXW10
QXF3D2850	QXF3D2850	28.5				85.5	115.5	175.5			
QXF3D2900	QXF3D2900	29.0				87	117	177			
QXF3D2950	QXF3D2950	29.5				88.5	118.5	178.5			
QXF3D3000	QXF3D3000	30.0				90	121	181			
QXF3D3050	QXF3D3050	30.5	32	55	60	91.5	122.5	182.5	SPMX 09	TXS3509	TXW10
QXF3D3100	QXF3D3100	31.0				93	124	184			
QXF3D3150	QXF3D3150	31.5				94.5	125.5	185.5			
QXF3D3200	QXF3D3200	32.0				96	127	187			
QXF3D3250	QXF3D3250	32.5				97.5	128.5	188.5			
QXF3D3300	QXF3D3300	33.0	32	55	60	99	130	190	SPMX 09	TXS3509	TXW10
QXF3D3400	QXF3D3400	34.0				102	133	193			
QXF3D3500	QXF3D3500	35.0				105	136	196			
QXF3D3600	QXF3D3600	36.0				108	139	199			
QXF3D3700	QXF3D3700	37.0				111	147	217			
QXF3D3800	QXF3D3800	38.0	40	58	70	114	151	221	SPMX 11	TXS4010	TXW15
QXF3D3900	QXF3D3900	39.0				117	154	224			
QXF3D4000	QXF3D4000	40.0				120	158	228			
QXF3D4100	QXF3D4100	41.0				123	162	232			
QXF3D4200	QXF3D4200	42.0				126	165	235			
QXF3D4300	QXF3D4300	43.0	40	58	70	129	169	239	SPMX 14	TXS5010	TXW20
QXF3D4400	QXF3D4400	44.0				132	172	242			
QXF3D4500	QXF3D4500	45.0				135	177	247			
QXF3D4600	QXF3D4600	46.0				138	181	251			
QXF3D4700	QXF3D4700	47.0				141	184	254			
QXF3D4800	QXF3D4800	48.0				144	188	258			
QXF3D4900	QXF3D4900	49.0				147	191	261			
QXF3D5000	QXF3D5000	50.0				150	195	265			

► ABS and Plain shanks available to order



INDEXABLE DRILLING
4 CORNER INSERT





UNIMASTER QX

Insert Type	
	SPMX 0602.. SPMX 07T3.. SPMX 0904..

EDP Code	TOOL CODE	DC	DMM	BD	LS	LU	LF	OAL	Insert	Screw	Wrench
QXF4D1600	QXF4D1600	16.0	25	32	56	64	85	141	SPMX 06	TXS2205	TXW07
QXF4D1700	QXF4D1700	17.0				68	89	145			
QXF4D1750	QXF4D1750	17.5				70	91	147			
QXF4D1800	QXF4D1800	18.0				72	93	149			
QXF4D1850	QXF4D1850	18.5				74	95	151			
QXF4D1900	QXF4D1900	19.0				76	97	153			
QXF4D1950	QXF4D1950	19.5				78	99	155			
QXF4D2000	QXF4D2000	20.0				80	102	158			
QXF4D2050	QXF4D2050	20.5				82	104	160			
QXF4D2100	QXF4D2100	21.0				84	106	162			
QXF4D2150	QXF4D2150	21.5				86	108	164			
QXF4D2200	QXF4D2200	22.0	32	45	60	88	118	178	SPMX 07	TXS2207	TXW08
QXF4D2250	QXF4D2250	22.5				90	120	180			
QXF4D2300	QXF4D2300	23.0				92	122	182			
QXF4D2350	QXF4D2350	23.5				94	124	184			
QXF4D2400	QXF4D2400	24.0				96	126	186			
QXF4D2450	QXF4D2450	24.5				98	128	188			
QXF4D2500	QXF4D2500	25.0				100	130	190			
QXF4D2550	QXF4D2550	25.5				102	132	192			
QXF4D2600	QXF4D2600	26.0				104	134	194			
QXF4D2650	QXF4D2650	26.5				106	136	196			
QXF4D2700	QXF4D2700	27.0				108	138	198			
QXF4D2750	QXF4D2750	27.5				110	140	200			

► ABS and Plain shanks available to order

INDEXABLE DRILLING
4 CORNER INSERT



UNIMASTER QX



Insert Type	
	SPMX 0602.. SPMX 07T3.. SPMX 0904..

EDP Code	TOOL CODE	DC	DMM	BD	LS	LU	LF	OAL	Insert	Screw	Wrench
QXF4D2800	QXF4D2800	28.0	32	45	60	112	142	202	SPMX 09	TXS3509	TXW10
QXF4D2850	QXF4D2850	28.5				114	144	204			
QXF4D2900	QXF4D2900	29.0				116	146	206			
QXF4D2950	QXF4D2950	29.5				118	148	208			
QXF4D3000	QXF4D3000	30.0				120	151	211			
QXF4D3050	QXF4D3050	30.5				122	153	213			
QXF4D3100	QXF4D3100	31.0				124	155	215			
QXF4D3150	QXF4D3150	31.5				126	157	217			
QXF4D3200	QXF4D3200	32.0				128	159	219			
QXF4D3250	QXF4D3250	32.5				130	161	221			
QXF4D3300	QXF4D3300	33.0				132	163	223			

► ABS and Plain shanks available to order



INDEXABLE DRILLING
4 CORNER INSERT





UNIMASTER QX

Insert Type	
	SPMX 0502.. SPMX 0602.. SPMX 07T3.. SPMX 0904.. SPMX 1104..

EDP Code	TOOL CODE	DC	DMM	BD	LS	LU	LF	OAL	Insert	Screw	Wrench
QXF5D1300	QXF5D1300	13.0	20	25	50	65	83	133	SPMX 05	TXS2043	TXW05
QXF5D1400	QXF5D1400	14.0				70	88	138			
QXF5D1500	QXF5D1500	15.0				75	93	143			
QXF5D1600	QXF5D1600	16.0	25	32	56	80	101	157	SPMX 06	TXS2205	TXW07
QXF5D1700	QXF5D1700	17.0				85	106	162			
QXF5D1800	QXF5D1800	18.0				90	111	167			
QXF5D1900	QXF5D1900	19.0				95	116	172			
QXF5D2000	QXF5D2000	20.0				100	122	178			
QXF5D2100	QXF5D2100	21.0				105	127	183			
QXF5D2200	QXF5D2200	22.0	32	45	60	110	140	200	SPMX 07	TXS2507	TXW08
QXF5D2300	QXF5D2300	23.0				115	145	205			
QXF5D2400	QXF5D2400	24.0				120	150	210			
QXF5D2500	QXF5D2500	25.0				125	155	215			
QXF5D2600	QXF5D2600	26.0				130	160	220			
QXF5D2700	QXF5D2700	27.0				135	165	225			
QXF5D2800	QXF5D2800	28.0	32	45	60	140	170	230	SPMX 09	TXS3509	TXW10
QXF5D2900	QXF5D2900	29.0		55		145	175	235			
QXF5D3000	QXF5D3000	30.0				150	181	241			
QXF5D3100	QXF5D3100	31.0				155	186	246			
QXF5D3200	QXF5D3200	32.0				160	191	251			
QXF5D3300	QXF5D3300	33.0				165	196	256			

► ABS and Plain shanks available to order

INDEXABLE DRILLING
4 CORNER INSERT



UNIMASTER QX



Insert Type	
	SPMX 0502.. SPMX 0602.. SPMX 07T3.. SPMX 0904.. SPMX 1104..

EDP Code	TOOL CODE	DC	DMM	BD	LS	LU	LF	OAL	Insert	Screw	wrench
QXF5D3400	QXF5D3400	34.0	40	54	70	170	203	273	SPMX 11	TXS4010	TXW15
QXF5D3500	QXF5D3500	35.0				175	209	279			
QXF5D3600	QXF5D3600	36.0				180	215	285			
QXF5D3700	QXF5D3700	37.0				185	221	291			
QXF5D3800	QXF5D3800	38.0				190	227	297			
QXF5D3900	QXF5D3900	39.0				195	232	302			
QXF5D4000	QXF5D4000	40.0				200	238	308			

► ABS and Plain shanks available to order



INDEXABLE DRILLING
4 CORNER INSERT, CARTRIDGE TYPE





Insert Type	
	SPMX 07T3.. SPMX 0904.. SPMX 1104.. SPMX 1405..

AVAILABLE ON REQUEST

EDP Code	TOOL CODE	DC	DMM	BD	LS	LU	LF	OAL	Insert	Screw	Wrench	Cartridge		Spacing Plate	Spacing Plate Screw
												Outer	Inner		
CXF25D5100	CXF25D5100	51.0	50	75	80	133	170	250	SPMX 07	TXS2507	TXW08	CA07P1	CA07C1	-	-
		52.0												P071	PS20043
		53.0												P072	
CXF25D5400	CXF25D5400	54.0				140	180	260	SPMX 07	TXS2507	TXW08	CA07P2	CA07C2	-	-
		55.0												P071	PS20043
		56.0												P072	
CXF25D5700	CXF25D5700	57.0				155	201	281	SPMX 09	TXS3509	TXW10	CA09P1	CA09C1	-	-
		58.0												P091	PS30055
		59.0												P092	
		60.0												P093	
		61.0												P094	
		62.0												P095	
CXF25D6300	CXF25D6300	63.0				165	215	295	SPMX 09	TXS3509	TXW10	CA09P2	CA09C2	-	-
		64.0												P091	PS30055
		65.0												P092	
		66.0												P093	
CXF25D6700	CXF25D6700	67.0				183	240	320	SPMX 11	TXS4010	TXW15	CA11P1	CA11C1	-	-
		68.0												P111	PS30055
		69.0												P112	
		70.0												P113	
		71.0												P114	
		72.0												P115	
		73.0												P116	



INDEXABLE DRILLING
4 CORNER INSERT, CARTRIDGE TYPE



Insert Type	
	SPMX 07T3.. SPMX 0904.. SPMX 1104.. SPMX 1405..

AVAILABLE ON REQUEST

EDP Code	TOOL CODE	DC	DMM	BD	LS	LU	LF	OAL	Insert	Screw	Wrench	Cartridge		Spacing Plate	Spacing Plate Screw
												Outer	Inner		
CXF25D7400	CXF25D7400	74.0	50	80	80	200	240	320	SPMX 11	TXS4010	TXW15	CA11D1	CA11M1	P091	PS30055
		79.0												P092	
CXF25D8000	CXF25D8000	80.0	50	84	80	213	253	333	SPMX 14	TXS5010	TXW20	CA14D	CA14M	P091	PS30055
		85.0												P092	
CXF25D8500	CXF25D8500	85.0	60	89	100	225	265	345	SPMX 14	TXS5010	TXW20	CA14D1	CA14M1	P091	PS30055
		90.0												P092	
CXF25D9000	CXF25D9000	90.0	60	94	100	235	275	355	SPMX 11	TXS4010	TXW15	CA11D2	CA11M2	P111	PS30055
		95.0												P112	
CXF25D9600	CXF25D9600	96.0	60	99	100	248	288	388	SPMX 11	TXS4010	TXW15	CA11D3	CA11M3	P111	PS30055
		100.0												P112	
CXF25D1010	CXF25D1010	101.0	60	104	100	260	300	400	SPMX 11	TXS4010	TXW15	CA11D4	CA11M4	P111	PS30055
		105.0												P112	
CXF25D1060	CXF25D1060	106.0	60	109	100	273	313	413	SPMX 14	TXS5010	TXW20	CA14D2	CA14M2	P111	PS30055
		111.0												P112	
CXF25D1120	CXF25D1120	112.0	60	114	100	285	325	425	SPMX 14	TXS5010	TXW20	CA14D3	CA14M3	P111	PS30055
		117.0												P112	

DRILLING






DRILLING



INDEXABLE DRILLING

3 CORNER INSERT, CARTRIDGE TYPE


UNIMASTER *HX*



AVAILABLE ON REQUEST

EDP Code	TOOL CODE	DC	DMM	LF	d	Insert	Screw	Wrench	Cartridge		Cartridge Screw
									Outer	Inner	
HXF7000	HXF7000	70.0	32	100	16	WCMX 08	TXS3511	TXW15	CA70P	CA70C	M6X20IMB
HXF7500	HXF7500	75.0							CA75P	CA75C	
HXF8000	HXF8000	80.0							CA80P	CA80C	
HXF8500	HXF8500	85.0							CA85P	CA85C	
HXF9000	HXF9000	90.0							CA90P	CA90C	
HXF9500	HXF9500	95.0							CA95P	CA95C	
HXF10000	HXF10000	100.0	42	105	20				CA100P	CA100C	M6X30IMB
HXF10500	HXF10500	105.0							CA105P	CA105C	
HXF11000	HXF11000	110.0							CA110P	CA110C	
HXF11500	HXF11500	115.0							CA115P	CA115C	
HXF12000	HXF12000	120.0	50						CA120P	CA120C	
HXF12500	HXF12500	125.0							CA125P	CA125C	
HXF13000	HXF13000	130.0							CA130P	CA130C	
HXF13500	HXF13500	135.0							CA135P	CA135C	
HXF14000	HXF14000	140.0							CA140P	CA140C	
HXF14500	HXF14500	145.0							CA145P	CA145C	
HXF15000	HXF15000	150.0							CA150P	CA150C	
HXF15500	HXF15500	155.0							CA155P	CA155C	
HXF16000	HXF16000	160.0	CA160P			CA160C					

INSERT	IC	S	INSERT	IC	S
SPMX 0502	5.0	2.38	SPMX 0904	9.8	4.30
SPMX 0602	6.0	2.38	SPMX 1104	11.5	4.90
SPMX 07T3	7.94	3.97	SPMX 1405	14.3	5.30




EDP Code DI..... Example: SPMX 050204-MS ET602 = DI00012

SPMX	ISO DESIGNATION	RE (mm)	f _n (mm/rev)	ET602	ET30P	K10A	K10T	K20A	K20T	P40A	P40T	T15A	T15T	M4A	M4T	M48A	M48T
				PVD													
	SPMX 050204-MS	0.4	0.02 - 0.11	● 00012													
	SPMX 060204-MS	0.4	0.03 - 0.11	● 00013													
	SPMX 07T308-MS	0.8	0.03 - 0.11	● 00014													
	SPMX 090408-MS	0.8	0.04 - 0.12	● 00015													
	SPMX 050204	0.4	0.05 - 0.14	● 00001													
	SPMX 060204	0.4	0.05 - 0.16	● 00002													
	SPMX 07T308	0.8	0.06 - 0.16	● 00003													
	SPMX 090408	0.8	0.06 - 0.16	● 00004													
	SPMX 110408	0.8	0.06 - 0.16	● 00005													
	SPMX 140512	1.2	0.06 - 0.18	● 00011													

ISO		P			M		K		N	S	H
MATERIAL		Non-alloy steel	Low alloy steel	High alloy steel	Ferritic / Martensitic Stainless steel	Austenitic Stainless steel	Grey Cast iron	Nodular Cast iron	Aluminium & Non-ferrous material	Heat Resistant and Super Alloys	Hardened steel
VDI GROUP		1-5	6-9	10-11	12-13	14	15-16	17-20	21-30	31-37	38
Vc (m/min)	ET602	140 - 240	120 - 220	70 - 150	140 - 250	120 - 200	140 - 220	150 - 240	250 - 600	24 - 45	40 - 80
	ET30P	58 - 126	47 - 95	42 - 68	-	-	79 - 131	79 - 131	-	-	-
	K10A	-	-	-	-	-	79 - 111	125 - 137	-	-	-
	K10T	-	-	-	-	-	56 - 75	80 - 98	-	-	-
	K20A	-	-	-	50 - 62	46 - 52	79 - 111	125 - 137	244 - 366	24 - 30	-
	K20T	-	-	-	42 - 50	38 - 44	56 - 75	80 - 98	291 - 427	20 - 26	-
	P40A	84 - 125	64 - 102	50 - 67	-	-	-	-	-	-	47 - 62
	P40T	52 - 101	83 - 82	37 - 50	-	-	-	-	-	-	37 - 49
	T15A	-	41 - 58	26 - 34	-	-	41 - 52	-	-	11 - 12	21 - 35
	T15T	-	36 - 42	19 - 25	-	-	29 - 35	-	-	8 - 9	16 - 19
	M4A	66 - 84	41 - 75	-	29 - 34	27 - 29	-	58 - 75	92 - 187	-	-
	M4T	45 - 63	36 - 52	-	20 - 24	18 - 20	-	42 - 52	137 - 244	-	-
	M48A	-	41 - 58	26 - 34	-	-	41 - 52	-	-	11 - 12	21 - 35
	M48T	-	36 - 42	19 - 25	-	-	29 - 35	-	-	8 - 9	16 - 19




INSERT	IC	S
WCMX 0402	6.35	2.38
WCMX 0503	7.94	3.18
WCMX 06T3	9.52	3.97
WCMX 0804	12.7	4.76



▶ EDP Code DI..... Example:WCMX 040208 ET602 = DI00007

P	●	●					●	○	●	●	●	●	●	●
M	●				●	○					●	○		
K	●	●	●	○	○	○					●	●	●	●
N	○				○	○	●				○	●		
S	●				○	○		●	○				●	○
H	○						○	○	○	○			○	○

WCMX	ISO DESIGNATION	RE (mm)	f _n (mm/rev)	ET602	ET30P	K10A	K10T	K20A	K20T	P40A	P40T	T15A	T15T	M4A	M4T	M48A	M48T
	WCMX 040208	0.8	0.05 - 0.13	● 00007													
	WCMX 050308	0.8	0.05 - 0.13	● 00008													
	WCMX 06T308	0.8	0.06 - 0.14	● 00009													
	WCMX 080412	1.2	0.06 - 0.16	● 00010													

UNIMASTER IX

Optimized flute design

- Excellent chip evacuation
- Body clearance to avoid clogging and workpiece contact
- Nickel plated for added wear resistance

Optimized point geometry

- Radius thinned point for chip breaking and self centering
- Negative land for high process reliability

Insert Grade ET30P


- Multi-layer PVD coating
- Optimised for thermal resistance and higher shear strength
- Tough carbide substrate, ideal for demanding applications

ISO		P			M		K		N	S	H
MATERIAL		Non-alloy steel	Low alloy steel	High alloy steel	Ferritic / Martensitic Stainless steel	Austenitic Stainless steel	Grey Cast iron	Nodular Cast iron	Aluminium & Non-ferrous material	Heat Resistant and Super Alloys	Hardened steel
VDI GROUP		1-5	6-9	10-11	12-13	14	15-16	17-20	21-30	31-37	38
VC (m/min)	ET602	140 - 240	120 - 220	70 - 150	140 - 250	120 - 200	140 - 220	150 - 240	250 - 600	24 - 45	40 - 80
	ET30P	58 - 126	47 - 95	42 - 68	-	-	79 - 131	79 - 131	-	-	-
	K10A	-	-	-	-	-	79 - 111	125 - 137	-	-	-
	K10T	-	-	-	-	-	56 - 75	80 - 98	-	-	-
	K20A	-	-	-	50 - 62	46 - 52	79 - 111	125 - 137	244 - 366	24 - 30	-
	K20T	-	-	-	42 - 50	38 - 44	56 - 75	80 - 98	291 - 427	20 - 26	-
	P40A	84 - 125	64 - 102	50 - 67	-	-	-	-	-	-	47 - 62
	P40T	52 - 101	83 - 82	37 - 50	-	-	-	-	-	-	37 - 49
	T15A	-	41 - 58	26 - 34	-	-	41 - 52	-	-	11 - 12	21 - 35
	T15T	-	36 - 42	19 - 25	-	-	29 - 35	-	-	8 - 9	16 - 19
	M4A	66 - 84	41 - 75	-	29 - 34	27 - 29	-	58 - 75	92 - 187	-	-
	M4T	45 - 63	36 - 52	-	20 - 24	18 - 20	-	42 - 52	137 - 244	-	-
	M48A	-	41 - 58	26 - 34	-	-	41 - 52	-	-	11 - 12	21 - 35
	M48T	-	36 - 42	19 - 25	-	-	29 - 35	-	-	8 - 9	16 - 19

Test Condition

Tool: **IXF14**
Method: **Blind hole**
Insert: **IX14**
Material: **42CrMo4 alloy steel (HRc30)**
v_c: **80 m/min**
n: **1820 rev/min**
f: **328 mm/min**
f_n: **0.18 mm/rev**
a_p: **65.0 mm (5xD)**
Coolant: **9% Emulsion**
Machine: **Vertical Machining Centre**

Result





Tool	Unimaster IX	COMPETITOR A	COMPETITOR B
No. of holes	240	180	240
Edge Condition	Wear	Chipped	Wear
Wear (µm)	22	300	60

Test was stopped at 240 holes, high spindle load from competitor B



INDEXABLE DRILLING
EXCHANGEABLE HEAD TYPE





UNIMASTER IX

Insert Series	
	IX10 to IX32

EDP Code	TOOL CODE	DC (Min)	DCX (Max)	DMM	BD	LS	LU	OAL	Insert Series	Screw	Wrench			
IXF3D1000	IXF3D1000	10.00	10.40	16	23	48	31.5	103.0	IX10	TXS1011	TXW05			
IXF3D1050	IXF3D1050	10.50	10.90				33.0	104.0						
IXF3D1100	IXF3D1100	11.00	11.40				34.5	105.0						
IXF3D1150	IXF3D1150	11.50	11.91				36.0	106.0						
IXF3D1200	IXF3D1200	12.00	12.40				37.5	109.8	IX12	TXS1213				
IXF3D1250	IXF3D1250	12.50	12.90				39.0	110.8						
IXF3D1300	IXF3D1300	13.00	13.49				40.5	112.8						
IXF3D1350	IXF3D1350	13.50	13.90				42.0	113.8						
IXF3D1400	IXF3D1400	14.00	14.40				43.5	116.3	IX14	TXS1415	TXW07			
IXF3D1450	IXF3D1450	14.50	14.90				45.0	118.3						
IXF3D1500	IXF3D1500	15.00	15.48				46.5	120.3						
IXF3D1550	IXF3D1550	15.50	15.90				48.0	121.3						
IXF3D1600	IXF3D1600	16.00	16.90	20	25	50	51.0	127.0	IX16	TXS1617				
IXF3D1700	IXF3D1700	17.00	17.90				54.0	130.0		TXS1718				
IXF3D1800	IXF3D1800	18.00	18.90	25	32	56	57.0	141.3	IX18	TXS1819	TXW09			
IXF3D1900	IXF3D1900	19.00	19.90				60.0	145.3		TXS1920				
IXF3D2000	IXF3D2000	20.00	20.90				63.0	147.5	IX20	TXS2021				
IXF3D2100	IXF3D2100	21.00	21.90				66.0	150.5		TXS2122				
IXF3D2200	IXF3D2200	22.00	22.90				69.0	153.4	IX22	TXS2223				
IXF3D2300	IXF3D2300	23.00	23.90				72.0	157.4		TXS2324				
IXF3D2400	IXF3D2400	24.00	24.90				32	37	60	75.0	165.8	IX24	TXS2425	TXW10
IXF3D2500	IXF3D2500	25.00	25.90							78.0	170.8		TXS2526	
IXF3D2600	IXF3D2600	26.00	26.99	81.0	172.2	IX26				TXS2627				
IXF3D2700	IXF3D2700	27.00	27.78	84.0	175.2					TXS2728				
IXF3D2800	IXF3D2800	28.00	28.97	87.0	179.2	IX28				TXS2829				
IXF3D2900	IXF3D2900	29.00	29.77	90.0	183.2					TXS2930				
IXF3D3000	IXF3D3000	30.00	30.96	93.0	187.0	IX30				TXS3031	TXW15			
IXF3D3100	IXF3D3100	31.00	31.75	96.0	191.0					TXS3132				
IXF3D3200	IXF3D3200	32.00	32.94	99.0	197.2	IX32	TXS3233							
IXF3D3300	IXF3D3300	33.00	33.73	102.0	201.2		TXS3334							



INDEXABLE DRILLING
EXCHANGEABLE HEAD TYPE



UNIMASTER IX



Insert Series	
	IX10 to IX32

EDP Code	TOOL CODE	DC (Min)	DCX (Max)	DMM	BD	LS	LU	OAL	Insert Series	Screw	Wrench
IXF5D1000	IXF5D1000	10.00	10.40	16	23	48	52.5	123.0	IX10	TXS1011	TXW05
IXF5D1050	IXF5D1050	10.50	10.90				55.0	125.0			
IXF5D1100	IXF5D1100	11.00	11.40				57.5	127.0			
IXF5D1150	IXF5D1150	11.50	11.91				60.0	129.0			
IXF5D1200	IXF5D1200	12.00	12.40				62.5	133.8	IX12	TXS1213	
IXF5D1250	IXF5D1250	12.50	12.90				65.0	135.8			
IXF5D1300	IXF5D1300	13.00	13.49				67.5	138.8			
IXF5D1350	IXF5D1350	13.50	13.90				70.0	140.8			
IXF5D1400	IXF5D1400	14.00	14.40				72.5	144.3	IX14	TXS1415	TXW07
IXF5D1450	IXF5D1450	14.50	14.90				75.0	147.3			
IXF5D1500	IXF5D1500	15.00	15.48				77.5	150.3			
IXF5D1550	IXF5D1550	15.50	15.90				80.0	152.3			
IXF5D1600	IXF5D1600	16.00	16.90	20	25	50	85.0	160.0	IX16	TXS1617	
IXF5D1700	IXF5D1700	17.00	17.90				90.0	165.0		TXS1718	
IXF5D1800	IXF5D1800	18.00	18.90	25	32	56	95.0	178.3	IX18	TXS1819	TXW09
IXF5D1900	IXF5D1900	19.00	19.90				100.0	184.3		TXS1920	
IXF5D2000	IXF5D2000	20.00	20.90				105.0	188.5	IX20	TXS2021	
IXF5D2100	IXF5D2100	21.00	21.90				110.0	193.5		TXS2122	
IXF5D2200	IXF5D2200	22.00	22.90				115.0	198.4	IX22	TXS2223	
IXF5D2300	IXF5D2300	23.00	23.90				120.0	204.4		TXS2324	
IXF5D2400	IXF5D2400	24.00	24.90	32	37	60	125.0	214.8	IX24	TXS2425	TXW10
IXF5D2500	IXF5D2500	25.00	25.90				130.0	221.8		TXS2526	
IXF5D2600	IXF5D2600	26.00	26.99				135.0	225.2	IX26	TXS2627	
IXF5D2700	IXF5D2700	27.00	27.78				140.0	230.2		TXS2728	
IXF5D2800	IXF5D2800	28.00	28.97				145.0	236.2	IX28	TXS2829	
IXF5D2900	IXF5D2900	29.00	29.77				150.0	242.2		TXS2930	
IXF5D3000	IXF5D3000	30.00	30.96				155.0	248.0	IX30	TXS3031	TXW15
IXF5D3100	IXF5D3100	31.00	31.75				160.0	254.0		TXS3132	
IXF5D3200	IXF5D3200	32.00	32.94				165.0	262.2	IX32	TXS3233	
IXF5D3300	IXF5D3300	33.00	33.73				170.0	268.2		TXS3334	

INDEXABLE DRILLING

EXCHANGEABLE HEAD TYPE

UNIMASTER IX



EDP Code	TOOL CODE	DC (Min)	DCX (Max)	DMM	BD	LS	LU	OAL	Insert Series	Screw	Wrench	
IXF8D1000	IXF8D1000	10.00	10.40	16	23	48	84.0	153.0	IX10	TXS1011	TXW05	
IXF8D1050	IXF8D1050	10.50	10.90				88.0	156.5				
IXF8D1100	IXF8D1100	11.00	11.40				92.0	160.0				
IXF8D1150	IXF8D1150	11.50	11.91				96.0	163.5				
IXF8D1200	IXF8D1200	12.00	12.40				100.0	169.8	IX12	TXS1213		
IXF8D1250	IXF8D1250	12.50	12.90				104.0	173.3				
IXF8D1300	IXF8D1300	13.00	13.49				108.0	177.8				
IXF8D1350	IXF8D1350	13.50	13.90				112.0	181.3				
IXF8D1400	IXF8D1400	14.00	14.40				116.0	186.3	IX14	TXS1415		TXW07
IXF8D1450	IXF8D1450	14.50	14.90				120.0	190.8				
IXF8D1500	IXF8D1500	15.00	15.48				124.0	195.3				
IXF8D1550	IXF8D1550	15.50	15.90				128.0	198.8				
IXF8D1600	IXF8D1600	16.00	16.90	20	25	50	136.0	209.5	IX16	TXS1617		
IXF8D1700	IXF8D1700	17.00	17.90				144.0	217.5		TXS1718		
IXF8D1800	IXF8D1800	18.00	18.90	25	32	56	152.0	233.8	IX18	TXS1819	TXW09	
IXF8D1900	IXF8D1900	19.00	19.90				160.0	242.8		TXS1920		
IXF8D2000	IXF8D2000	20.00	20.90				168.0	250.0	IX20	TXS2021		
IXF8D2100	IXF8D2100	21.00	21.90				176.0	258.0		TXS2122		
IXF8D2200	IXF8D2200	22.00	22.90				184.0	265.9	IX22	TXS2223		
IXF8D2300	IXF8D2300	23.00	23.90				192.0	274.9		TXS2324		
IXF8D2400	IXF8D2400	24.00	24.90	32	37	60	200.0	288.3	IX24	TXS2425	TXW10	
IXF8D2500	IXF8D2500	25.00	25.90				208.0	298.3		TXS2526		
IXF8D2600	IXF8D2600	26.00	26.99				216.0	304.7	IX26	TXS2627		
IXF8D2700	IXF8D2700	27.00	27.78				224.0	312.7		TXS2728		
IXF8D2800	IXF8D2800	28.00	28.97				232.0	321.7	IX28	TXS2829		
IXF8D2900	IXF8D2900	29.00	29.77				240.0	330.7		TXS2930		
IXF8D3000	IXF8D3000	30.00	30.96				248.0	339.5	IX30	TXS3031		TXW15
IXF8D3100	IXF8D3100	31.00	31.75				256.0	348.5		TXS3132		
IXF8D3200	IXF8D3200	32.00	32.94				264.0	359.7	IX32	TXS3233		
IXF8D3300	IXF8D3300	33.00	33.73				272.0	368.7		TXS3334		

► EDP Code IX.Z..... Example: Series IX10 10.00mm ET30P = IX10Z1000

P	●	●					●	○	●	●	●	●	●	●
M	●				●	○					●	○		
K	●	●	●	○	○	○					●	●	●	●
N	○				○	●					○	●		
S	●				○	○			●	○			●	○
H	○						○	○	○	○			○	○

▶ IX10 Series No. IX10Z

▶ IX12 Series No. IX12Z

[illegible]

ISO		P			M		K		N	S	H
MATERIAL		Non-alloy steel	Low alloy steel	High alloy steel	Ferritic / Martensitic Stainless steel	Austenitic Stainless steel	Grey Cast iron	Nodular Cast iron	Aluminium & Non-ferrous material	Heat Resistant and Super-Alloys	Hardened steel
VDI GROUP		1-5	6-9	10-11	12-13	14	15-16	17-20	21-30	31-37	38
Vc (m/min)	ET30P	58 - 126	47 - 95	42 - 68	-	-	79 - 131	79 - 131	-	-	-



► EDP Code IX..Z..... Example: Series IX12 13.20mm ET30P = IX12Z1320

- IX10 Series No. IX10Z
- IX12 Series No. IX12Z
- IX16 Series No. IX16Z

P	●	●					●	○	●	●	●	●	●	●	●
M	●	●				●	○				●	○			
K	●	●	●	○	○	○					●	●	●	●	●
N	○				○	●					○	●			
S	●				○	○			●	○			●	○	
H	○						○	○	○	○			○	○	

IX	SERIES	ORD Code	Size	f _n (mm/rev)	ET602	ET30P	K10A	K10T	K20A	K20T	P40A	P40T	T15A	T15T	M4A	M4T	M48A	M48T
					PVD													
	IX12	-1320	13.20	0.09 - 0.29		●												
		-1330	13.30			●												
		-1340	13.40			●												
		-1350	13.50			●												
		-1360	13.60			●												
		-1370	13.70			●												
		-1380	13.80			●												
		-1390	13.90			●												
	IX14	-1400	14.00	0.09 - 0.29		●												
		-1410	14.10			●												
		-1420	14.20			●												
		-1430	14.30			●												
		-1440	14.40			●												
		-1450	14.50			●												
		-1460	14.60			●												
		-1470	14.70			●												
		-1480	14.80	0.12 - 0.41		●												
		-1490	14.90			●												
		-1500	15.00			●												
		-1510	15.10			●												
		-1520	15.20			●												
		-1530	15.30			●												
		-1540	15.40			●												
		-1550	15.50			●												
		-1560	15.60			●												
		-1570	15.70			●												
		-1580	15.80			●												
		-1590	15.90			●												
	IX16	-1600	16.00	0.12 - 0.41		●												
		-1610	16.10			●												
		-1620	16.20			●												
		-1630	16.30			●												

ISO		P			M		K		N	S	H	
MATERIAL		Non-alloy steel	Low alloy steel	High alloy steel	Ferritic / Martensitic Stainless steel	Austenitic Stainless steel	Grey Cast iron	Nodular Cast iron	Aluminium & Non-ferrous material	Heat Resistant and Super Alloys	Hardened steel	
	VDI GROUP		1-5	6-9	10-11	12-13	14	15-16	17-20	21-30	31-37	38
	v_c (m/min)	ET30P	58 - 126	47 - 95	42 - 68	-	-	79 - 131	79 - 131	-	-	-



► EDP Code IX..Z..... Example: Series IX16 16.40mm ET30P = IX16Z1640

- IX16 Series No. IX16Z
- IX18 Series No. IX18Z

P	●	●					●	○	●	●	●	●	●	●	●
M	●	●				●	○				●	○			
K	●	●	●	○	○	○					●	●	●	●	●
N	○				○	●					○	●			
S	●				○	○			●	○			●	○	
H	○						○	○	○	○			○	○	

IX	SERIES	ORD Code	Size	f _n (mm/rev)	ET602	ET30P	K10A	K10T	K20A	K20T	P40A	P40T	T15A	T15T	M4A	M4T	M48A	M48T
					PVD													
	IX16	-1640	16.40	0.12 - 0.41		●												
		-1650	16.50			●												
		-1660	16.60			●												
		-1670	16.70			●												
		-1680	16.80			●												
		-1690	16.90			●												
		-1700	17.00			●												
		-1710	17.10			●												
		-1720	17.20			●												
		-1730	17.30			●												
		-1740	17.40			●												
		-1750	17.50			●												
		-1760	17.60			●												
		-1770	17.70			●												
		-1780	17.80			●												
		-1790	17.90			●												
	IX18	-1800	18.00	0.20 - 0.46		●												
		-1810	18.10			●												
		-1820	18.20			●												
		-1830	18.30			●												
		-1840	18.40			●												
		-1850	18.50			●												
		-1860	18.60			●												
		-1870	18.70			●												
		-1880	18.80			●												
		-1890	18.90			●												
		-1900	19.00			●												
		-1910	19.10			●												
		-1920	19.20			●												
		-1930	19.30			●												
		-1940	19.40			●												
		-1950	19.50			●												

ISO		P			M		K		N	S	H
MATERIAL		Non-alloy steel	Low alloy steel	High alloy steel	Ferritic / Martensitic Stainless steel	Austenitic Stainless steel	Grey Cast iron	Nodular Cast iron	Aluminium & Non-ferrous material	Heat Resistant and Super Alloys	Hardened steel
VDI GROUP		1-5	6-9	10-11	12-13	14	15-16	17-20	21-30	31-37	38
V _c (m/min)	ET30P	58 - 126	47 - 95	42 - 68	-	-	79 - 131	79 - 131	-	-	-

DRILLING



► EDP Code IX..Z..... Example: Series IX18 19.60mm ET30P = IX18Z1960

P	●	●						●	○	●	●	●	●	●	●
M	●	●									●	○			
K	●	●	●	○	○	○						●	●	●	●
N	○				○	●					○	●			
S	●				○	○		●	○				●	○	
H	○						○	○	○	○			○	○	

- IX18 Series No. IX18Z
- IX20 Series No. IX20Z
- IX22 Series No. IX22Z

IX	SERIES	ORD Code	Size	f _n (mm/rev)	ET602	ET30P	K10A	K10T	K20A	K20T	P40A	P40T	T15A	T15T	M4A	M4T	M48A	M48T
	IX18	-1960	19.60	0.20 - 0.46	PVD													
		-1970	19.70		●													
		-1980	19.80		●													
		-1990	19.90		●													
	IX20	-2000	20.00	0.20 - 0.46	●													
		-2010	20.10		●													
		-2020	20.20		●													
		-2030	20.30		●													
		-2040	20.40		●													
		-2050	20.50		●													
		-2060	20.60		●													
		-2070	20.70		●													
		-2080	20.80		●													
		-2090	20.90		●													
		-2100	21.00		●													
		-2110	21.10		●													
		-2120	21.20		●													
		-2130	21.30		●													
		-2140	21.40		●													
		-2150	21.50		●													
		-2160	21.60		●													
		-2170	21.70		●													
		-2180	21.80		●													
		-2190	21.90		●													
	IX22	-2200	22.00	0.22 - 0.57	●													
		-2210	22.10		●													
		-2220	22.20		●													
		-2230	22.30		●													
		-2240	22.40		●													
		-2250	22.50		●													
		-2260	22.60		●													
		-2270	22.70		●													

ISO		P			M		K		N	S	H	
MATERIAL		Non-alloy steel	Low alloy steel	High alloy steel	Ferritic / Martensitic Stainless steel	Austenitic Stainless steel	Grey Cast iron	Nodular Cast iron	Aluminium & Non-ferrous material	Heat Resistant and Super Alloys	Hardened steel	
	VDI GROUP		1-5	6-9	10-11	12-13	14	15-16	17-20	21-30	31-37	38
	v_c (m/min)	ET30P	58 - 126	47 - 95	42 - 68	-	-	79 - 131	79 - 131	-	-	-

DRILLING



► EDP Code IX..Z..... Example: Series IX22 22.80mm ET30P = IX22Z22800

P	●	●						●	○	●	●	●	●	●	●
M	●	●									●	○			
K	●	●	●	○	○	○						●	●	●	●
N	○				○	●					○	●			
S	●				○	○		●	○				●	○	
H	○						○	○	○	○			○	○	

- IX22 Series No. IX22Z
- IX24 Series No. IX24Z

IX	SERIES	ORD Code	Size	f _n (mm/rev)	ET602	ET30P	K10A	K10T	K20A	K20T	P40A	P40T	T15A	T15T	M4A	M4T	M48A	M48T
	IX22	-2280	22.80	0.22 - 0.57	PVD													
		-2290	22.90		●													
		-2300	23.00		●													
		-2310	23.10		●													
		-2320	23.20		●													
		-2330	23.30		●													
		-2340	23.40		●													
		-2350	23.50		●													
		-2360	23.60		●													
		-2370	23.70		●													
		-2380	23.80		●													
		-2390	23.90		●													
	IX24	-2400	24.00	0.22 - 0.57	●													
		-2410	24.10		●													
		-2420	24.20		●													
		-2430	24.30		●													
		-2440	24.40		●													
		-2450	24.50		●													
		-2460	24.60		●													
		-2470	24.70		●													
		-2480	24.80		●													
		-2490	24.90		●													
		-2500	25.00		●													
		-2510	25.10		●													
		-2520	25.20		●													
		-2530	25.30		●													
		-2540	25.40		●													
		-2550	25.50		●													
		-2560	25.60		●													
		-2570	25.70		●													
		-2580	25.80		●													
		-2590	25.90		●													

ISO		P			M		K		N	S	H
MATERIAL		Non-alloy steel	Low alloy steel	High alloy steel	Ferritic / Martensitic Stainless steel	Austenitic Stainless steel	Grey Cast iron	Nodular Cast iron	Aluminium & Non-ferrous material	Heat Resistant and Super Alloys	Hardened steel
VDI GROUP		1-5	6-9	10-11	12-13	14	15-16	17-20	21-30	31-37	38
V _c (m/min)	ET30P	58 - 126	47 - 95	42 - 68	-	-	79 - 131	79 - 131	-	-	-



- ▶ IX26 Series No. IX26Z
- ▶ IX28 Series No. IX28Z
- ▶ IX30 Series No. IX30Z
- ▶ IX32 Series No. IX32Z

▶ EDP Code IX..Z..... Example: Series IX26 26.0mm ET30P = IX26Z2600																	
P	●	●						●	○	●	●	●	●	●	●	●	●
M	●					●	○							●	○		
K	●	●	●	○	○	○	○							●	●	●	●
N	○				○	●								○	●		
S	●				○	○				●	○					●	○
H	○							○	○	○	○					○	○
Drill bit illustration IX SERIES ORD Code Size f_n (mm/rev)	ET602	ET30P	K10A	K10T	K20A	K20T	P40A	P40T	T15A	T15T	M4A	M4T	M48A	M48T			
	PVD																
	0.57		●														
			●														
			●														
			●														
	0.61		●														
			●														
			●														
			●														
	0.61		●														
			●														
			●														
			●														
	0.61		●														
			●														
		●															
		●															

ISO		P			M		K		N	S	H
MATERIAL		Non-alloy steel	Low alloy steel	High alloy steel	Ferritic / Martensitic Stainless steel	Austenitic Stainless steel	Grey Cast iron	Nodular Cast iron	Aluminium & Non-ferrous material	Heat Resistant and Super Alloys	Hardened steel
VDI GROUP		1-5	6-9	10-11	12-13	14	15-16	17-20	21-30	31-37	38
V _c (m/min)	ET30P	58 - 126	47 - 95	42 - 68	-	-	79 - 131	79 - 131	-	-	-

TYPICAL DRILLING ISSUES


	ANGLED SURFACE • Reduce feed when starting • <5° reduce by ≤30% • <10° reduce by ≤40% • <25° reduce by ≤50% • >25° reduce by ≤60% • Use shortest drill possible • If possible, use flat bottom carbide drill or spade drill
	ANGLED EXIT • At point of exit, reduce feed by ≤50%
	CROSS BORE • Reduce feed by ≤50% at start of interrupted cut • Increase feed once cross bore has been cleared • Be wary of chip clogging
	STACKED DRILLING • Plates must be clamped rigidly • Maximum permissible gap 0.5mm - 1.0mm
	UNEVEN SURFACE • Reduce feed when starting by ≤50% depending on depth of unevenness • If possible, spot face surface first
	CHAIN DRILLING • Drill holes 1 & 2 first • When drilling hole 3, reduce feed by ≤50% to cater for interrupted cut • Make overlap <1.5mm on diameter if possible



SPADE DRILLING - STRAIGHT SHANK

STRAIGHT FLUTE, STUB

- Inserts: Carbide - pages 161-166
- Inserts: HSS - pages 167-183



TOOL CODE	DC (Min)	DCX (Max)	LU	LB	LF	OAL	DMM	LS	CNT(R)	CNT(S)	Holder Type	Insert Series
8Y115016FM	9.50	11.00	19.1	47.6	50.0	89.5	16.0	41.9	1/16"	1/8"	Y	Y
8Z115016FM	11.11	12.70	19.1	47.6	50.0	89.5	16.0	41.9	1/16"	1/8"	Z	Z
80115020FM	13.00	17.65	22.2	47.6	50.4	89.5	20.0	41.9	1/8"	1/8"	0	0
81115020FM	15.50	17.65	22.2	47.6	50.4	89.5	20.0	41.9	1/8"	1/8"	0.5	0
82115025FM	17.86	24.00	47.6	75.8	79.4	128.9	25.0	53.1	1/8"	1/8"	1	1
83115025FM	22.00	24.00	57.2	88.5	92.1	141.6	25.0	53.1	1/8"	1/8"	1.5	1
84115032FM	24.61	35.00	57.2	88.5	92.1	146.4	32.0	57.9	1/4"	1/8"	2	2

FOR HOLDER TYPE	TORX SCREW	TORX DRIVER
Y	TXS2004	TXW07
Z	TXS2005	TXW07
0, 0.5	TXS25065	TXW08
1, 1.5	TXS3007	TXW09
2	TXS40095	TXW15


** Note : Replacement screws in packs of 10



SPADE DRILLING - STRAIGHT SHANK

STRAIGHT FLUTE, SHORT

- Inserts: Carbide - pages 161-166
- Inserts: HSS - pages 167-183



TOOL CODE	DC (Min)	DCX (Max)	LU	LB	LF	OAL	DMM	LS	CNT	Holder Type	Insert Series
8Y215020FM	9.50	11.00	31.8	61.1	63.5	103.0	20.0	41.9	1/8"	Y	Y
8Z215020FM	11.11	12.70	31.8	61.1	63.5	103.0	20.0	41.9	1/8"	Z	Z
80215020FM	13.00	17.65	34.9	63.5	66.3	105.4	20.0	41.9	1/8"	0	0
81215020FM	15.50	17.65	34.9	63.5	66.3	105.4	20.0	41.9	1/8"	0.5	0
82215025FM	17.86	24.00	66.7	107.2	110.7	160.2	25.0	53.1	1/8"	1	1
83215025FM	22.00	24.00	66.7	107.2	110.7	160.2	25.0	53.1	1/8"	1.5	1
84215032FM	24.61	35.00	85.7	128.6	132.2	186.5	32.0	57.9	1/4"	2	2
85215032FM	30.00	35.00	85.7	128.6	132.2	186.5	32.0	57.9	1/4"	2.5	2
86215040FM	35.72	47.63	120.7	173.0	177.8	243.1	40.0	70.1	1/4"	3	3
87215040FM	48.00	65.09	130.2	179.4	184.2	249.5	40.0	70.1	1/4"	4	4

FOR HOLDER TYPE	TORX SCREW	TORX DRIVER
Y	TXS2004	TXW07
Z	TXS2005	TXW07
0, 0.5	TXS25065	TXW08
1, 1.5	TXS3007	TXW09
2, 2.5	TXS40095	TXW15
3, 4	TXS5015	TXW20


** Note : Replacement screws in packs of 10



SPADE DRILLING - STRAIGHT SHANK

SPIRAL FLUTE, INTERMEDIATE

- ▶ Inserts: Carbide - pages 161-166
- ▶ Inserts: HSS - pages 167-183



TOOL CODE	DC (Min)	DCX (Max)	LU	LB	LF	OAL	DMM	LS	CNT	Holder Type	Insert Series
82325025FM	17.86	24.00	117.5	154.8	158.4	207.9	25.0	53.1	1/8"	1	1
83325025FM	22.00	24.00	117.5	154.8	158.4	207.9	25.0	53.1	1/8"	1.5	1
84325032FM	24.61	35.00	136.5	179.4	183.0	237.3	32.0	57.9	1/4"	2	2
85325032FM	30.00	35.00	136.5	179.4	183.0	237.3	32.0	57.9	1/4"	2.5	2
86325040FM	35.72	47.63	165.1	217.5	222.3	287.6	40.0	70.1	1/4"	3	3

FOR HOLDER TYPE	TORX SCREW	TORX DRIVER
1, 1.5	TXS3007	TXW09
2, 2.5	TXS40095	TXW15
3	TXS5015	TXW20


** Note : Replacement screws in packs of 10



SPADE DRILLING - STRAIGHT SHANK

SPIRAL FLUTE, STANDARD

- ▶ Inserts: Carbide - pages 161-166
- ▶ Inserts: HSS - pages 167-183



TOOL CODE	DC (Min)	DCX (Max)	LU	LB	LF	OAL	DMM	LS	CNT	Holder Type	Insert Series
8Y325020FM	9.50	11.00	60.3	89.7	92.1	131.6	20.0	41.9	1/8"	Y	Y
8Z425020FM	11.11	12.70	60.3	89.7	92.1	131.6	20.0	41.9	1/8"	Z	Z
80425020FM	13.00	17.65	63.5	92.1	94.9	134.0	20.0	41.9	1/8"	0	0
81425020FM	15.50	17.65	63.5	92.1	94.9	134.0	20.0	41.9	1/8"	0.5	0
82425025FM	17.86	24.00	168.3	205.6	209.2	258.7	25.0	53.1	1/8"	1	1
83425025FM	22.00	24.00	168.3	205.6	209.2	258.7	25.0	53.1	1/8"	1.5	1
84425032FM	24.61	35.00	187.3	230.2	233.8	288.1	32.0	57.9	1/4"	2	2
85425032FM	30.00	35.00	187.3	230.2	233.8	288.1	32.0	57.9	1/4"	2.5	2
86425040FM	35.72	47.63	209.6	261.9	266.7	332.0	40.0	70.1	1/4"	3	3
87425040FM	48.00	65.09	231.8	281.0	285.8	351.1	40.0	70.1	1/4"	4	4

FOR HOLDER TYPE	TORX SCREW	TORX DRIVER
Y	TXS2004	TXW07
Z	TXS2005	TXW07
0, 0.5	TXS25065	TXW08
1, 1.5	TXS3007	TXW09
2, 2.5	TXS40095	TXW15
3, 4	TXS5015	TXW20


** Note : Replacement screws in packs of 10



SPADE DRILLING - STRAIGHT SHANK

SPIRAL FLUTE, EXTENDED

- Inserts: Carbide - pages 161-166
- Inserts: HSS - pages 167-183



TOOL CODE	DC (Min)	DCX (Max)	LU	LB	LF	OAL	DMM	LS	CNT	Holder Type	Insert Series
8Y425020FM	9.50	11.00	111.1	140.5	142.9	182.4	20.0	41.9	1/8"	Y	Y
8Z525020FM	11.11	12.70	111.1	140.5	142.9	182.4	20.0	41.9	1/8"	Z	Z
80525020FM	13.00	17.65	114.3	142.9	145.7	184.8	20.0	41.9	1/8"	0	0
81525020FM	15.50	17.65	114.3	142.9	145.7	184.8	20.0	41.9	1/8"	0.5	0
82525025FM	17.86	24.00	269.9	307.2	310.8	360.3	25.0	53.1	1/8"	1	1
83525025FM	22.00	24.00	269.9	307.2	310.8	360.3	25.0	53.1	1/8"	1.5	1
84525032FM	24.61	35.00	288.9	331.8	335.4	389.7	32.0	57.9	1/4"	2	2
85525032FM	30.00	35.00	288.9	331.8	335.4	389.7	32.0	57.9	1/4"	2.5	2

FOR HOLDER TYPE	TORX SCREW	TORX DRIVER
Y	TXS2004	TXW07
Z	TXS2005	TXW07
0, 0.5	TXS25065	TXW08
1, 1.5	TXS3007	TXW09
2, 2.5	TXS40095	TXW15


** Note : Replacement screws in packs of 10



SPADE DRILLING - STRAIGHT SHANK

STRAIGHT FLUTE, EXTENDED

- Inserts: Carbide - pages 161-166
- Inserts: HSS - pages 167-183



TOOL CODE	DC (Min)	DCX (Max)	LU	LB	LF	OAL	DMM	LS	CNT	Holder Type	Insert Series
86515040FM	35.72	47.63	349.3	401.6	406.4	471.7	40.0	70.1	1/4"	3	3
87515040FM	48.00	65.09	422.3	471.5	476.3	541.6	40.0	70.1	1/4"	4	4


FOR HOLDER TYPE	TORX SCREW	TORX DRIVER
3, 4	TXS5015	TXW20

** Note : Replacement screws in packs of 10



SPADE DRILLING - TAPER SHANK
STRAIGHT FLUTE, SHORT

- ▶ Inserts: Carbide - pages 161-166
- ▶ Inserts: HSS - pages 167-183



TOOL CODE	DC (Min)	DCX (Max)	LU	LB	LF	OAL	DCON (MT)	CNT	RCA	Holder Type	Insert Series
8Y2150002M	9.50	11.00	31.7	51.5	88.0	160.3	#2	1/16"	SP0107	Y	Y
8Z2150002M	11.11	12.70	31.7	51.5	88.0	160.3	#2	1/16"	SP0107	Z	Z
802150002M	13.00	17.65	34.9	55.5	92.4	164.3	#2	1/16"	SP0107	0	0
812150002M	15.50	17.65	34.9	55.5	92.4	164.3	#2	1/16"	SP0107	0.5	0
822150003M	17.86	24.00	69.8	98.4	142.5	232.5	#3	1/8"	SP0108	1	1
832150003M	22.00	24.00	69.8	98.4	142.5	232.5	#3	1/8"	SP0108	1.5	1
842150004M	24.61	35.00	85.7	114.3	160.4	273.8	#4	1/8"	SP0108	2	2
852150004M	30.00	35.00	85.7	114.3	167.6	281.0	#4	1/4"	SP0109	2.5	2
862150004M	35.72	47.63	120.6	152.4	206.4	319.1	#4	1/4"	SP0109	3	3
872150005M	48.00	65.09	130.1	165.1	219.1	363.5	#5	1/4"	SP0110	4	4
882150005M	63.50	88.90	171.1	215.9	287.3	430.2	#5	1/2"	SP0111	5	5, 6
892150005M	89.69	114.30	171.1	225.4	296.8	439.7	#5	1/2"	SP0111	7	7, 8

▶ Rotary Coolant Apaptor can be applied for internal cooling, refer to page 143


FOR HOLDER TYPE	TORX SCREW	TORX DRIVER
Y	TXS2004	TXW07
Z	TXS2005	TXW07
0, 0.5	TXS25065	TXW08
1, 1.5	TXS3007	TXW09
2, 2.5	TXS40095	TXW15
3, 4	TXS5015	TXW20
5, 7	TXS6019	TXW25

** Note : Replacement screws in packs of 10



SPADE DRILLING - TAPER SHANK
SPIRAL FLUTE, INTERMEDIATE

- ▶ Inserts: Carbide - pages 161-166
- ▶ Inserts: HSS - pages 167-183



TOOL CODE	DC (Min)	DCX (Max)	LU	LB	LF	OAL	DCON (MT)	CNT	RCA	Holder Type	Insert Series
823250003M	17.86	24.00	120.7	149.2	193.3	283.3	#3	1/8"	SP0108	1	1
833250003M	22.00	24.00	120.7	149.2	193.3	283.3	#3	1/8"	SP0108	1.5	1
843250004M	24.61	35.00	136.5	165.1	211.2	324.6	#4	1/8"	SP0108	2	2
853250004M	30.00	35.00	136.5	165.1	218.4	331.8	#4	1/4"	SP0109	2.5	2
863250004M	35.72	47.63	165.1	196.9	250.9	363.6	#4	1/4"	SP0109	3	3

▶ Rotary Coolant Apaptor can be applied for internal cooling, refer to page 143


FOR HOLDER TYPE	TORX SCREW	TORX DRIVER
1, 1.5	TXS3007	TXW09
2, 2.5	TXS40095	TXW15
3	TXS5015	TXW20

** Note : Replacement screws in packs of 10

SPADE DRILLING - TAPER SHANK

SPIRAL FLUTE, STANDARD

- Inserts: Carbide - pages 161-166
- Inserts: HSS - pages 167-183



TOOL CODE	DC (Min)	DCX (Max)	LU	LB	LF	OAL	DCON (MT)	CNT	RCA	Holder Type	Insert Series
8Y4250002M	9.50	11.00	60.3	80.2	116.7	188.9	#2	1/16"	SP0107	Y	Y
8Z4250002M	11.11	12.70	60.3	80.2	116.7	188.9	#2	1/16"	SP0107	Z	Z
804250002M	13.00	17.65	63.5	84.1	121.0	192.9	#2	1/16"	SP0107	0	0
814250002M	15.50	17.65	63.5	84.1	121.0	192.9	#2	1/16"	SP0107	0.5	0
824250003M	17.86	24.00	171.5	200.0	244.1	334.2	#3	1/8"	SP0108	1	1
834250003M	22.00	24.00	171.5	200.0	244.1	334.2	#3	1/8"	SP0108	1.5	1
844250004M	24.61	35.00	187.3	215.9	262.0	375.4	#4	1/8"	SP0108	2	2
854250004M	30.00	35.00	187.3	215.9	269.2	382.6	#4	1/4"	SP0109	2.5	2
864250004M	35.72	47.63	209.5	241.3	295.3	408.0	#4	1/4"	SP0109	3	3
874250005M	48.00	65.09	231.8	266.7	320.7	465.1	#5	1/4"	SP0110	4	4
884250005M	63.50	88.90	273.1	317.5	388.9	531.8	#5	1/2"	SP0111	5	5, 6
894250005M	89.69	114.30	273.1	327.0	398.5	541.3	#5	1/2"	SP0111	7	7, 8

Rotary Coolant Apaptor can be applied for internal cooling, refer to page 143


FOR HOLDER TYPE	TORX SCREW	TORX DRIVER
Y	TXS2004	TXW07
Z	TXS2005	TXW07
0, 0.5	TXS25065	TXW08
1, 1.5	TXS3007	TXW09
2, 2.5	TXS40095	TXW15
3, 4	TXS5015	TXW20
5, 7	TXS6019	TXW25

** Note : Replacement screws in packs of 10

SPADE DRILLING - TAPER SHANK

SPIRAL FLUTE, EXTENDED

- Inserts: Carbide - pages 161-166
- Inserts: HSS - pages 167-183



TOOL CODE	DC (Min)	DCX (Max)	LU	LB	LF	OAL	DCON (MT)	CNT	RCA	Holder Type	Insert Series
8Y5250002M	9.50	11.00	111.1	130.9	167.4	239.7	#2	1/16"	SP0107	Y	Y
8Z5250002M	11.11	12.70	111.1	130.9	167.4	239.7	#2	1/16"	SP0107	Z	Z
805250002M	13.00	17.65	114.3	135.0	171.8	243.7	#2	1/16"	SP0107	0	0
815250002M	15.50	17.65	114.3	135.0	171.8	243.7	#2	1/16"	SP0107	0.5	0
825250003M	17.86	24.00	273.1	301.6	345.7	435.8	#3	1/8"	SP0108	1	1
835250003M	22.00	24.00	273.1	301.6	345.7	435.8	#3	1/8"	SP0108	1.5	1
845250004M	24.61	35.00	289.0	317.5	363.6	477.0	#4	1/8"	SP0108	2	2
855250004M	30.00	35.00	289.0	317.5	370.8	484.2	#4	1/4"	SP0109	2.5	2

Rotary Coolant Apaptor can be applied for internal cooling, refer to page 143


FOR HOLDER TYPE	TORX SCREW	TORX DRIVER
Y	TXS2004	TXW07
Z	TXS2005	TXW07
0, 0.5	TXS25065	TXW08
1, 1.5	TXS3007	TXW09
2, 2.5	TXS40095	TXW15

** Note : Replacement screws in packs of 10



SPADE DRILLING - TAPER SHANK
STRAIGHT FLUTE, STANDARD


- ▶ Inserts: Carbide - pages 161-166
- ▶ Inserts: HSS - pages 167-183



TOOL CODE	DC (Min)	DCX (Max)	LU	LB	LF	OAL	DCON (MT)	CNT	RCA	Holder Type	Insert Series
865150004M	35.72	47.63	349.3	381.0	435.0	547.7	#4	1/4"	SP0109	3	3
875150005M	48.00	65.09	422.3	457.2	511.2	655.6	#5	1/4"	SP0110	4	4
885150005M	63.50	88.90	463.6	508.0	579.4	722.3	#5	1/2"	SP0111	5	5, 6
895150005M	89.69	114.30	555.6	609.6	681.1	823.9	#5	1/2"	SP0111	7	7, 8

▶ Rotary Coolant Apaptor can be applied for internal cooling, refer to page 143

ROTARY COOLANT ADAPTOR
FOR TAPER SHANK SPADE DRILLS



TOOL CODE	DCB	BD	WB	THFT	CNT
SP0107	19.05	44.45	22.23	M8 X 1.25	1/8"
SP0108	25.40	53.97	28.57	M8 X 1.25	1/8"
SP0109	31.75	63.50	34.92	M10 X 1.5	1/4"
SP0110	44.45	76.20	34.92	M10 X 1.5	1/4"
SP0111	57.15	95.27	44.45	M12 X 1.75	1/2"

Thread to BSP & ISO 7-1

FOR HOLDER TYPE	TORX SCREW	TORX DRIVER
3, 4	TXS5015	TXW20
5, 7	TXS6019	TXW25

** Note : Replacement screws in packs of 10

DRILLING



DRILLING



► EDP Code example: P40A 4F 18.00mm = 8345231800

P	●	●					●	○	●	●	●	●	●	●	●
M	●					●	○				●	○			
K	●	●	●	○	○	○					●	○	●	●	●
N	○				○	●					○	●			
S	●				○	○		●	○				●	○	
H	○						○	○	○	○			○	○	

► Series No. 834523

CARBIDE 4F POINT	SERIES	ORD Code	Size	f _n (mm/rev)	ET602	ET30P	K10A	K10T	K20A	K20T	P40A	P40T	T15A	T15T	M4A	M4T	M48A	M48T
					PVD													
	1	-1800	18.00	0.20 - 0.36							●							
		-1850	18.50								●							
		-1900	19.00								●							
		-1950	19.50								●							
		-2000	20.00								●							
		-2050	20.50								●							
		2100	21.00								●							
		-2200	22.00								●							
		-2300	23.00								●							
		-2400	24.00								●							
	2	-2500	25.00	0.27 - 0.44							●							
		-2600	26.00								●							
		-2700	27.00								●							
		-2800	28.00								●							
		-2900	29.00								●							
		-3000	30.00								●							
		-3100	31.00								●							
		-3200	32.00								●							
		-3300	33.00								●							
		-3400	34.00								●							
		-3500	35.00								●							

► EDP Code example: P40A 4F 36.00mm = 8345233600

P	●	●					●	○	●	●	●	●	●	●	●
M	●					●	○				●	○			
K	●	●	●	○	○	○					●	○	●	●	●
N	○				○	●					○	●			
S	●				○	○		●	○				●	○	
H	○						○	○	○	○			○	○	

► Series No. 834523

CARBIDE 4F POINT	SERIES	ORD Code	Size	f _n (mm/rev)	ET602	ET30P	K10A	K10T	K20A	K20T	P40A	P40T	T15A	T15T	M4A	M4T	M48A	M48T
					PVD													
	3	-3600	36.00	0.30 - 0.50							●							
		-3700	37.00								●							
		-3800	38.00								●							
		-3900	39.00								●							
		-4000	40.00								●							
		-4100	41.00								●							
		-4200	42.00								●							
		-4300	43.00								●							
		-4400	44.00								●							
		-4500	45.00								●							
		-4600	46.00								●							
		-4700	47.00								●							

ISO		P			M		K		N	S	H
MATERIAL		Non-alloy steel	Low alloy steel	High alloy steel	Ferritic / Martensitic Stainless steel	Austenitic Stainless steel	Grey Cast iron	Nodular Cast iron	Aluminium & Non-ferrous material	Heat Resistant and Super Alloys	Hardened steel
VDI GROUP		1-5	6-9	10-11	12-13	14	15-16	17-20	21-30	31-37	38
V _c (m/min)	K10A	-	-	-	-	-	79 - 111	125 - 137	-	-	-
	K10T	-	-	-	-	-	56 - 75	80 - 98	-	-	-
	K20A	-	-	-	50 - 62	46 - 52	79 - 111	125 - 137	244 - 366	24 - 30	-
	K20T	-	-	-	42 - 50	38 - 44	56 - 75	80 - 98	291 - 427	20 - 26	-
	P40A	84 - 125	64 - 102	50 - 67	-	-	-	-	-	-	47 - 62
	P40T	52 - 101	83 - 82	37 - 50	-	-	-	-	-	-	37 - 49
	T15A	-	41 - 58	26 - 34	-	-	41 - 52	-	-	11 - 12	21 - 35
	T15T	-	36 - 42	19 - 25	-	-	29 - 35	-	-	8 - 9	16 - 19
	M4A	66 - 84	41 - 75	-	29 - 34	27 - 29	-	58 - 75	92 - 187	-	-
	M4T	45 - 63	36 - 52	-	20 - 24	18 - 20	-	42 - 52	137 - 244	-	-
	M48A	-	41 - 58	26 - 34	-	-	41 - 52	-	-	11 - 12	21 - 35
	M48T	-	36 - 42	19 - 25	-	-	29 - 35	-	-	8 - 9	16 - 19

ISO		P			M		K		N	S	H
MATERIAL		Non-alloy steel	Low alloy steel	High alloy steel	Ferritic / Martensitic Stainless steel	Austenitic Stainless steel	Grey Cast iron	Nodular Cast iron	Aluminium & Non-ferrous material	Heat Resistant and Super Alloys	Hardened steel
VDI GROUP		1-5	6-9	10-11	12-13	14	15-16	17-20	21-30	31-37	38
V _c (m/min)	K10A	-	-	-	-	-	79 - 111	125 - 137	-	-	-
	K10T	-	-	-	-	-	56 - 75	80 - 98	-	-	-
	K20A	-	-	-	50 - 62	46 - 52	79 - 111	125 - 137	244 - 366	24 - 30	-
	K20T	-	-	-	42 - 50	38 - 44	56 - 75	80 - 98	291 - 427	20 - 26	-
	P40A	84 - 125	64 - 102	50 - 67	-	-	-	-	-	-	47 - 62
	P40T	52 - 101	83 - 82	37 - 50	-	-	-	-	-	-	37 - 49
	T15A	-	41 - 58	26 - 34	-	-	41 - 52	-	-	11 - 12	21 - 35
	T15T	-	36 - 42	19 - 25	-	-	29 - 35	-	-	8 - 9	16 - 19
	M4A	66 - 84	41 - 75	-	29 - 34	27 - 29	-	58 - 75	92 - 187	-	-
	M4T	45 - 63	36 - 52	-	20 - 24	18 - 20	-	42 - 52	137 - 244	-	-
	M48A	-	41 - 58	26 - 34	-	-	41 - 52	-	-	11 - 12	21 - 35
	M48T	-	36 - 42	19 - 25	-	-	29 - 35	-	-	8 - 9	16 - 19

DRILLING



- ▶ K10A Series No. 832323
- ▶ K10T Series No. 832308
- ▶ K20A Series No. 830323
- ▶ K20T Series No. 830308
- ▶ P40A Series No. 831323
- ▶ P40T Series No. 831308

▶ EDP Code example: K10A 9.50mm = 8323230950

P	●	●						●	○	●	●	●	●	●	●
M	●	●					●	○			●	○			
K	●	●	●	○	○	○					●	●	●	●	●
N	○	○			○	○					○	●			
S	●				○	○			●	○			●	○	
H	○					○	○	○	○				○	○	

CARBIDE	SERIES	ORD Code	Size	f _n (mm/rev)	ET602	ET30P	K10A	K10T	K20A	K20T	P40A	P40T	T15A	T15T	M4A	M4T	M48A	M48T
	Y	-0950	9.50	0.10 - 0.24	PVD													
		-0980	9.80				●	●	●	●	●	●						
		-1000	10.00				●	●	●	●	●	●						
		-1020	10.20				●	●	●	●	●	●						
		-1050	10.50				●	●	●	●	●	●						
		-1080	10.80				●	●	●	●	●	●						
		-1100	11.00				●	●	●	●	●	●						
	Z	-1150	11.50	0.10 - 0.24			●	●	●	●	●	●						
		-1200	12.00				●	●	●	●	●	●						
		-1250	12.50				●	●	●	●	●	●						
	0	-1300	13.00	0.14 - 0.38			●	●	●	●	●	●						
		-1350	13.50				●	●	●	●	●	●						
		-1400	14.00				●	●	●	●	●	●						
		-1450	14.50				●	●	●	●	●	●						
		-1500	15.00				●	●	●	●	●	●						
		-1550	15.50				●	●	●	●	●	●						
		-1600	16.00				●	●	●	●	●	●						
		-1650	16.50				●	●	●	●	●	●						
		-1700	17.00				●	●	●	●	●	●						
		-1750	17.50				●	●	●	●	●	●						

DRILLING



- ▶ K10A Series No. 832323
- ▶ K10T Series No. 832308
- ▶ K20A Series No. 830323
- ▶ K20T Series No. 830308
- ▶ P40A Series No. 831323
- ▶ P40T Series No. 831308

▶ EDP Code example: K10A 18.00mm = 8323231800

P	●	●						●	○	●	●	●	●	●	●
M	●	●					●	○			●	○			
K	●	●	●	○	○	○					●	●	●	●	●
N	○	○			○	○					○	●			
S	●				○	○			●	○			●	○	
H	○					○	○	○	○				○	○	

CARBIDE	SERIES	ORD Code	Size	f _n (mm/rev)	ET602	ET30P	K10A	K10T	K20A	K20T	P40A	P40T	T15A	T15T	M4A	M4T	M48A	M48T
	1	-1800	18.00	0.18 - 0.45	PVD													
		-1850	18.50				●	●	●	●	●	●						
		-1900	19.00				●	●	●	●	●	●						
		-1950	19.50				●	●	●	●	●	●						
		-2000	20.00				●	●	●	●	●	●						
		-2050	20.50				●	●	●	●	●	●						
		2100	21.00				●	●	●	●	●	●						
		-2200	22.00				●	●	●	●	●	●						
		-2300	23.00				●	●	●	●	●	●						
		-2400	24.00				●	●	●	●	●	●						
	2	-2500	25.00	0.19 - 0.50			●	●	●	●	●	●						
		-2600	26.00				●	●	●	●	●	●						
		-2700	27.00				●	●	●	●	●	●						
		-2800	28.00				●	●	●	●	●	●						
		-2900	29.00				●	●	●	●	●	●						
		-3000	30.00				●	●	●	●	●	●						
		-3100	31.00				●	●	●	●	●	●						
		-3200	32.00				●	●	●	●	●	●						
		-3300	33.00				●	●	●	●	●	●						
		-3400	34.00				●	●	●	●	●	●						
		-3500	35.00				●	●	●	●	●	●						

ISO	P			M		K		N	S	H
MATERIAL	Non-alloy steel	Low alloy steel	High alloy steel	Ferritic / Martensitic Stainless steel	Austenitic Stainless steel	Grey Cast iron	Nodular Cast iron	Aluminium & Non-ferrous material	Heat Resistant and Super Alloys	Hardened steel
VDI GROUP	1-5	6-9	10-11	12-13	14	15-16	17-20	21-30	31-37	38
V _c (m/min)	K10A	-	-	-	-	79 - 111	125 - 137	-	-	-
	K10T	-	-	-	-	56 - 75	80 - 98	-	-	-
	K20A	-	-	-	50 - 62	46 - 52	79 - 111	125 - 137	24 - 30	-
	K20T	-	-	-	42 - 50	38 - 44	56 - 75	80 - 98	20 - 26	-
	P40A	84 - 125	64 - 102	50 - 67	-	-	-	-	-	47 - 62
	P40T	52 - 101	83 - 82	37 - 50	-	-	-	-	-	37 - 49
	T15A	-	41 - 58	26 - 34	-	-	41 - 52	-	11 - 12	21 - 35
	T15T	-	36 - 42	19 - 25	-	-	29 - 35	-	8 - 9	16 - 19
	M4A	66 - 84	41 - 75	-	29 - 34	27 - 29	-	58 - 75	92 - 187	-
	M4T	45 - 63	36 - 52	-	20 - 24	18 - 20	-	42 - 52	137 - 244	-
	M48A	-	41 - 58	26 - 34	-	-	41 - 52	-	11 - 12	21 - 35
	M48T	-	36 - 42	19 - 25	-	-	29 - 35	-	8 - 9	16 - 19

ISO	P			M		K		N	S	H
MATERIAL	Non-alloy steel	Low alloy steel	High alloy steel	Ferritic / Martensitic Stainless steel	Austenitic Stainless steel	Grey Cast iron	Nodular Cast iron	Aluminium & Non-ferrous material	Heat Resistant and Super Alloys	Hardened steel
VDI GROUP	1-5	6-9	10-11	12-13	14	15-16	17-20	21-30	31-37	38
V _c (m/min)	K10A	-	-	-	-	79 - 111	125 - 137	-	-	-
	K10T	-	-	-	-	56 - 75	80 - 98	-	-	-
	K20A	-	-	-	50 - 62	46 - 52	79 - 111	125 - 137	24 - 30	-
	K20T	-	-	-	42 - 50	38 - 44	56 - 75	80 - 98	20 - 26	-
	P40A	84 - 125	64 - 102	50 - 67	-	-	-	-	-	47 - 62
	P40T	52 - 101	83 - 82	37 - 50	-	-	-	-	-	37 - 49
	T15A	-	41 - 58	26 - 34	-	-	41 - 52	-	11 - 12	21 - 35
	T15T	-	36 - 42	19 - 25	-	-	29 - 35	-	8 - 9	16 - 19
	M4A	66 - 84	41 - 75	-	29 - 34	27 - 29	-	58 - 75	92 - 187	-
	M4T	45 - 63	36 - 52	-	20 - 24	18 - 20	-	42 - 52	137 - 244	-
	M48A	-	41 - 58	26 - 34	-	-	41 - 52	-	11 - 12	21 - 35
	M48T	-	36 - 42	19 - 25	-	-	29 - 35	-	8 - 9	16 - 19

- ▶ P40A Series No. 831323
- ▶ P40T Series No. 831308

vc
(m/min)

► EDP Code example: T15A 4F 9.50mm = 8343270950

► Series No. 834327

vc
(m/min)

DRILLING



DRILLING



► EDP Code example: T15A 4F 18.00mm = 8343271800

P	●	●						●	○	●	●	●	●	●	●
M	●	●									●	○			
K	●	●	●	○	○	○				○		●	●	●	●
N	○				○	●					○	●			
S	●				○	○				●	○			●	○
H	○						○	○	○	○			○	○	

► Series No. 834327

HSS 4F POINT	SERIES	ORD Code	Size	f _n (mm/rev)	ET602	ET30P	K10A	K10T	K20A	K20T	P40A	P40T	T15A	T15T	M4A	M4T	M48A	M48T
					PVD													
	1	-1800	18.00	0.16 - 0.40									●					
		-1850	18.50										●					
		-1900	19.00										●					
		-1950	19.50										●					
		-2000	20.00										●					
		-2050	20.50										●					
		2100	21.00										●					
		-2200	22.00										●					
		-2300	23.00										●					
		-2400	24.00										●					
	2	-2500	25.00	0.19 - 0.49									●					
		-2600	26.00										●					
		-2700	27.00										●					
		-2800	28.00										●					
		-2900	29.00										●					
		-3000	30.00										●					
		-3100	31.00										●					
		-3200	32.00										●					
		-3300	33.00										●					
		-3400	34.00										●					
		-3500	35.00										●					

► EDP Code example: T15A 4F 36.00mm = 83432733600

P	●	●						●	○	●	●	●	●	●	●
M	●	●										●	○		
K	●	●	●	○	○	○				○		●	●	●	●
N	○				○	●					○	●			
S	●				○	○				●	○			●	○
H	○						○	○	○	○			○	○	

► Series No. 834327

HSS 4F POINT	SERIES	ORD Code	Size	f _n (mm/rev)	ET602	ET30P	K10A	K10T	K20A	K20T	P40A	P40T	T15A	T15T	M4A	M4T	M48A	M48T
					PVD													
	3	-3600	36.00	0.25 - 0.59									●					
		-3700	37.00										●					
		-3800	38.00										●					
		-3900	39.00										●					
		-4000	40.00										●					
		-4100	41.00										●					
		-4200	42.00										●					
		-4300	43.00										●					
		-4400	44.00										●					
		-4500	45.00										●					
		-4600	46.00										●					
		-4700	47.00										●					

ISO		P			M		K		N	S	H
MATERIAL		Non-alloy steel	Low alloy steel	High alloy steel	Ferritic / Martensitic Stainless steel	Austenitic Stainless steel	Grey Cast iron	Nodular Cast iron	Aluminium & Non-ferrous material	Heat Resistant and Super Alloys	Hardened steel
VDI GROUP		1-5	6-9	10-11	12-13	14	15-16	17-20	21-30	31-37	38
Vc (m/min)	K10A	-	-	-	-	-	79 - 111	125 - 137	-	-	-
	K10T	-	-	-	-	-	56 - 75	80 - 98	-	-	-
	K20A	-	-	-	50 - 62	46 - 52	79 - 111	125 - 137	244 - 366	24 - 30	-
	K20T	-	-	-	42 - 50	38 - 44	56 - 75	80 - 98	291 - 427	20 - 26	-
	P40A	84 - 125	64 - 102	50 - 67	-	-	-	-	-	-	47 - 62
	P40T	52 - 101	83 - 82	37 - 50	-	-	-	-	-	-	37 - 49
	T15A	-	41 - 58	26 - 34	-	-	41 - 52	-	-	11 - 12	21 - 35
	T15T	-	36 - 42	19 - 25	-	-	29 - 35	-	-	8 - 9	16 - 19
	M4A	66 - 84	41 - 75	-	29 - 34	27 - 29	-	58 - 75	92 - 187	-	-
	M4T	45 - 63	36 - 52	-	20 - 24	18 - 20	-	42 - 52	137 - 244	-	-
	M48A	-	41 - 58	26 - 34	-	-	41 - 52	-	-	11 - 12	21 - 35
	M48T	-	36 - 42	19 - 25	-	-	29 - 35	-	-	8 - 9	16 - 19

ISO		P			M		K		N	S	H
MATERIAL		Non-alloy steel	Low alloy steel	High alloy steel	Ferritic / Martensitic Stainless steel	Austenitic Stainless steel	Grey Cast iron	Nodular Cast iron	Aluminium & Non-ferrous material	Heat Resistant and Super Alloys	Hardened steel
VDI GROUP		1-5	6-9	10-11	12-13	14	15-16	17-20	21-30	31-37	38
Vc (m/min)	K10A	-	-	-	-	-	79 - 111	125 - 137	-	-	-
	K10T	-	-	-	-	-	56 - 75	80 - 98	-	-	-
	K20A	-	-	-	50 - 62	46 - 52	79 - 111	125 - 137	244 - 366	24 - 30	-
	K20T	-	-	-	42 - 50	38 - 44	56 - 75	80 - 98	291 - 427	20 - 26	-
	P40A	84 - 125	64 - 102	50 - 67	-	-	-	-	-	-	47 - 62
	P40T	52 - 101	83 - 82	37 - 50	-	-	-	-	-	-	37 - 49
	T15A	-	41 - 58	26 - 34	-	-	41 - 52	-	-	11 - 12	21 - 35
	T15T	-	36 - 42	19 - 25	-	-	29 - 35	-	-	8 - 9	16 - 19
	M4A	66 - 84	41 - 75	-	29 - 34	27 - 29	-	58 - 75	92 - 187	-	-
	M4T	45 - 63	36 - 52	-	20 - 24	18 - 20	-	42 - 52	137 - 244	-	-
	M48A	-	41 - 58	26 - 34	-	-	41 - 52	-	-	11 - 12	21 - 35
	M48T	-	36 - 42	19 - 25	-	-	29 - 35	-	-	8 - 9	16 - 19

DRILLING



► EDP Code example: T15A FLAT 9.50mm = 8283270950

P	●	●						●	○	●	●	●	●	●	●
M	●							○		○	●	○			
K	●	●	●	○	○	○					●	●	●	●	●
N	○				○	●		○		○	○	●			
S	●				○	○		○	○	○			○	○	
H	○						○	○	○	○			○	○	

► Series No. 828327

HSS FLAT	SERIES	ORD Code	Size	f _n (mm/rev)	ET602	ET30P	K10A	K10T	K20A	K20T	P40A	P40T	T15A	T15T	M4A	M4T	M48A	M48T
	Y	-0950	9.50	0.05 - 0.13	PVD													
		-0980	9.80										●					
		-1000	10.00										●					
		-1020	10.20										●					
		-1050	10.50										●					
		-1080	10.80										●					
		-1100	11.00										●					
	Z	-1150	11.50	0.05 - 0.13									●					
		-1200	12.00										●					
		-1250	12.50										●					
	0	-1300	13.00	0.10 - 0.25									●					
		-1350	13.50										●					
		-1400	14.00										●					
		-1450	14.50										●					
		-1500	15.00										●					
		-1550	15.50										●					
		-1600	16.00										●					
		-1650	16.50										●					
		-1700	17.00										●					
		-1750	17.50										●					

DRILLING



► EDP Code example: T15A FLAT 18.00mm = 8283271800

P	●	●						●	○	●	●	●	●	●	●
M	●							○		○	●	○			
K	●	●	●	○	○	○				○	○	●	●	●	●
N	○				○	●		○		○	○	○	●		
S	●				○	○		○	○	○	○	○		○	○
H	○						○	○	○	○	○	○		○	○

► Series No. 828327

HSS FLAT	SERIES	ORD Code	Size	f _n (mm/rev)	ET602	ET30P	K10A	K10T	K20A	K20T	P40A	P40T	T15A	T15T	M4A	M4T	M48A	M48T
	1	-1800	18.00	0.12 - 0.35	PVD													
		-1850	18.50										●					
		-1900	19.00										●					
		-1950	19.50										●					
		-2000	20.00										●					
		-2050	20.50										●					
		2100	21.00										●					
		-2200	22.00										●					
		-2300	23.00										●					
		-2400	24.00										●					
	2	-2500	25.00	0.18 - 0.41									●					
		-2600	26.00										●					
		-2700	27.00										●					
		-2800	28.00										●					
		-2900	29.00										●					
		-3000	30.00										●					
		-3100	31.00										●					
		-3200	32.00										●					
		-3300	33.00										●					
		-3400	34.00										●					
		-3500	35.00										●					

ISO	P			M		K		N	S	H
MATERIAL	Non-alloy steel	Low alloy steel	High alloy steel	Ferritic / Martensitic Stainless steel	Austenitic Stainless steel	Grey Cast iron	Nodular Cast iron	Aluminium & Non-ferrous material	Heat Resistant and Super Alloys	Hardened steel
VDI GROUP	1-5	6-9	10-11	12-13	14	15-16	17-20	21-30	31-37	38
V _c (m/min)	K10A	-	-	-	-	79 - 111	125 - 137	-	-	-
	K10T	-	-	-	-	56 - 75	80 - 98	-	-	-
	K20A	-	-	-	50 - 62	46 - 52	79 - 111	125 - 137	24 - 30	-
	K20T	-	-	-	42 - 50	38 - 44	56 - 75	80 - 98	20 - 26	-
	P40A	84 - 125	64 - 102	50 - 67	-	-	-	-	-	47 - 62
	P40T	52 - 101	83 - 82	37 - 50	-	-	-	-	-	37 - 49
	T15A	-	41 - 58	26 - 34	-	-	41 - 52	-	11 - 12	21 - 35
	T15T	-	36 - 42	19 - 25	-	-	29 - 35	-	8 - 9	16 - 19
	M4A	66 - 84	41 - 75	-	29 - 34	27 - 29	-	58 - 75	92 - 187	-
	M4T	45 - 63	36 - 52	-	20 - 24	18 - 20	-	42 - 52	137 - 244	-
	M48A	-	41 - 58	26 - 34	-	-	41 - 52	-	11 - 12	21 - 35
	M48T	-	36 - 42	19 - 25	-	-	29 - 35	-	8 - 9	16 - 19

ISO	P			M		K		N	S	H
MATERIAL	Non-alloy steel	Low alloy steel	High alloy steel	Ferritic / Martensitic Stainless steel	Austenitic Stainless steel	Grey Cast iron	Nodular Cast iron	Aluminium & Non-ferrous material	Heat Resistant and Super Alloys	Hardened steel
VDI GROUP	1-5	6-9	10-11	12-13	14	15-16	17-20	21-30	31-37	38
V _c (m/min)	K10A	-	-	-	-	79 - 111	125 - 137	-	-	-
	K10T	-	-	-	-	56 - 75	80 - 98	-	-	-
	K20A	-	-	-	50 - 62	46 - 52	79 - 111	125 - 137	24 - 30	-
	K20T	-	-	-	42 - 50	38 - 44	56 - 75	80 - 98	20 - 26	-
	P40A	84 - 125	64 - 102	50 - 67	-	-	-	-	-	47 - 62
	P40T	52 - 101	83 - 82	37 - 50	-	-	-	-	-	37 - 49
	T15A	-	41 - 58	26 - 34	-	-	41 - 52	-	11 - 12	21 - 35
	T15T	-	36 - 42	19 - 25	-	-	29 - 35	-	8 - 9	16 - 19
	M4A	66 - 84	41 - 75	-	29 - 34	27 - 29	-	58 - 75	92 - 187	-
	M4T	45 - 63	36 - 52	-	20 - 24	18 - 20	-	42 - 52	137 - 244	-
	M48A	-	41 - 58	26 - 34	-	-	41 - 52	-	11 - 12	21 - 35
	M48T	-	36 - 42	19 - 25	-	-	29 - 35	-	8 - 9	16 - 19

DRILLING



► EDP Code example: T15A 9.50mm = 8083270950

- T15A Series No. 808327
- T15T Series No. 808317
- M48A Series No. 809321
- M48T Series No. 809305

P															
M															
K															
N															
S															
H															

HSS	SERIES	ORD Code	Size mm	Size Inch	f _n (mm/rev)	K10A	K10T	K20A	K20T	P40A	P40T	T15A	T15T	M4A	M4T	M48A	M48T
	Y	-0950	9.50		0.06 - 0.16							●	●			●	●
		-0953	9.53	3/8								●	●			●	●
		-0980	9.80									●	●			●	●
		-0992	9.92	25/64								●	●			●	●
		-1000	10.00									●	●			●	●
		-1020	10.20									●	●			●	●
		-1032	10.32	13/32								●	●			●	●
		-1050	10.50									●	●			●	●
		-1072	10.72	27/64								●	●			●	●
		-1080	10.80									●	●			●	●
		-1100	11.00									●	●			●	●
	Z	-1111	11.11	7/16	0.06 - 0.16							●	●			●	●
		-1150	11.50									●	●			●	●
		-1151	11.51	29/64								●	●			●	●
		-1191	11.91	15/32								●	●			●	●
		-1200	12.00									●	●			●	●
		-1230	12.30	31/64								●	●			●	●
		-1250	12.50									●	●			●	●
		-1270	12.70	1/2								●	●			●	●

ISO	P			M		K		N	S	H
MATERIAL	Non-alloy steel	Low alloy steel	High alloy steel	Ferritic / Martensitic Stainless steel	Austenitic Stainless steel	Grey Cast iron	Nodular Cast iron	Aluminium & Non-ferrous material	Heat Resistant and Super Alloys	Hardened steel
VDI GROUP	1-5	6-9	10-11	12-13	14	15-16	17-20	21-30	31-37	38
V _c (m/min)	K10A	-	-	-	-	79 - 111	125 - 137	-	-	-
	K10T	-	-	-	-	56 - 75	80 - 98	-	-	-
	K20A	-	-	-	50 - 62	46 - 52	79 - 111	125 - 137	24 - 30	-
	K20T	-	-	-	42 - 50	38 - 44	56 - 75	80 - 98	20 - 26	-
	P40A	84 - 125	64 - 102	50 - 67	-	-	-	-	-	47 - 62
	P40T	52 - 101	83 - 82	37 - 50	-	-	-	-	-	37 - 49
	T15A	-	41 - 58	26 - 34	-	-	41 - 52	-	11 - 12	21 - 35
	T15T	-	36 - 42	19 - 25	-	-	29 - 35	-	8 - 9	16 - 19
	M4A	66 - 84	41 - 75	-	29 - 34	27 - 29	-	58 - 75	92 - 187	-
	M4T	45 - 63	36 - 52	-	20 - 24	18 - 20	-	42 - 52	137 - 244	-
	M48A	-	41 - 58	26 - 34	-	-	41 - 52	-	11 - 12	21 - 35
	M48T	-	36 - 42	19 - 25	-	-	29 - 35	-	8 - 9	16 - 19

DRILLING



► EDP Code example: T15A 13.00mm = 8083271300

- T15A Series No. 808327
- T15T Series No. 808317
- M48A Series No. 809321
- M48T Series No. 809305

P															
M															
K															
N															
S															
H															

HSS	SERIES	ORD Code	Size mm	Size Inch	f _n (mm/rev)	K10A	K10T	K20A	K20T	P40A	P40T	T15A	T15T	M4A	M4T	M48A	M48T
	0	-1300	13.00		0.14 - 0.30							●	●			●	●
		-1310	13.10	33/64								●	●			●	●
		-1349	13.49	17/32								●	●			●	●
		-1350	13.50									●	●			●	●
		-1389	13.89	35/64								●	●			●	●
		-1400	14.00									●	●			●	●
		-1429	14.29	9/16								●	●			●	●
		-1450	14.50									●	●			●	●
		-1468	14.68	37/64								●	●			●	●
		-1500	15.00									●	●			●	●
		-1508	15.08	19/32								●	●			●	●
		-1548	15.48	39/64								●	●			●	●
		-1550	15.50									●	●			●	●
		-1588	15.88	5/8								●	●			●	●
		-1600	16.00									●	●			●	●
		-1627	16.27	41/64								●	●			●	●
		-1650	16.50									●	●			●	●
		-1667	16.67	21/32								●	●			●	●
		-1700	17.00									●	●			●	●
		-1707	17.07	43/64								●	●			●	●
		-1746	17.46	11/16								●	●			●	●
		-1750	17.50									●	●			●	●

ISO	P			M		K		N	S	H
MATERIAL	Non-alloy steel	Low alloy steel	High alloy steel	Ferritic / Martensitic Stainless steel	Austenitic Stainless steel	Grey Cast iron	Nodular Cast iron	Aluminium & Non-ferrous material	Heat Resistant and Super Alloys	Hardened steel
VDI GROUP	1-5	6-9	10-11	12-13	14	15-16	17-20	21-30	31-37	38
V _c (m/min)	K10A	-	-	-	-	79 - 111	125 - 137	-	-	-
	K10T	-	-	-	-	56 - 75	80 - 98	-	-	-
	K20A	-	-	-	50 - 62	46 - 52	79 - 111	125 - 137	24 - 30	-
	K20T	-	-	-	42 - 50	38 - 44	56 - 75	80 - 98	20 - 26	-
	P40A	84 - 125	64 - 102	50 - 67	-	-	-	-	-	47 - 62
	P40T	52 - 101	83 - 82	37 - 50	-	-	-	-	-	37 - 49
	T15A	-	41 - 58	26 - 34	-	-	41 - 52	-	11 - 12	21 - 35
	T15T	-	36 - 42	19 - 25	-	-	29 - 35	-	8 - 9	16 - 19
	M4A	66 - 84	41 - 75	-	29 - 34	27 - 29	-	58 - 75	92 - 187	-
	M4T	45 - 63	36 - 52	-	20 - 24	18 - 20	-	42 - 52	137 - 244	-
	M48A	-	41 - 58	26 - 34	-	-	41 - 52	-	11 - 12	21 - 35
	M48T	-	36 - 42	19 - 25	-	-	29 - 35	-	8 - 9	16 - 19

- EDP Code example: T15A 1.17/32 = 8083273096

P					●	○	●	●	●	●	●	●
M			●	○					●	○		
K	●	○	○	○					●	●	●	●
N			○	●					○	●		
S			○	○			●	○			●	○
H					○	○	○	○			○	○

HSS	SERIES	ORD Code	Size mm	Size Inch	f _η (mm/rev)	K10A	K10T	K20A	K20T	P40A	P40T	T15A	T15T	M4A	M4T	M48A	M48T
	2	-3096	30.96	1.7/32	0.19 - 0.50							●	●	●	●	●	●
		-3100	31.00									●	●	●	●	●	●
		-3175	31.75	1.1/4								●	●	●	●	●	●
		-3200	32.00									●	●	●	●	●	●
		-3254	32.54	1.9/32								●	●	●	●	●	●
		-3300	33.00									●	●	●	●	●	●
		-3334	33.34	1.5/16								●	●	●	●	●	●
		-3400	34.00									●	●	●	●	●	●
		-3413	34.13	1.11/32								●	●	●	●	●	●
		-3493	34.93	1.3/8								●	●	●	●	●	●
		-3500	35.00									●	●	●	●	●	●
	3	-3572	35.72	1.13/32	0.25 - 0.59							●	●	●	●		
		-3600	36.00									●	●	●	●		
		-3651	36.51	1.7/16								●	●	●	●		
		-3700	37.00									●	●	●	●		
		-3731	37.31	1.15/32								●	●	●	●		
		-3800	38.00									●	●	●	●		
		-3810	38.10	1.1/2								●	●	●	●		
		-3889	38.89	1.17/32								●	●	●	●		
		-3900	39.00									●	●	●	●		
		-3969	39.69	1.9/16								●	●	●	●		
		-4000	40.00									●	●	●	●		

176 Europa Tool Co.,Ltd

- EDP Code example: T15A 1.19/32 = 8083274048

P					●	○	●	●	●	●	●	●
M			●	○					●	○		●
K	●	○	○	○					●	●	●	●
N			○	●					○	●		
S			○	○			●	○			●	○
H					○	○	○	○			○	○

Europa Tool Co.,Ltd 177

► EDP Code example: T15A 1.31/32 = 8083275001

P					●	○	●	●	●	●	●	●
M			●	○						○		
K	●	○	○	○					●	●	●	●
N			○	●					○	●		
S			○	○			●	○			●	○
H					○	○	○	○			○	○

VC
(m/min)

► EDP Code example: T15A 60.00mm = 808327600

P						●	○	●	●	●	●	●	●
M				●	○					●	○		
K	●	○		○	○					●	●	●	●
N				○	●					○	●		
S				○	○			●	○			●	○
H						○	○	○	○			○	○

VC
(m/min)

DRILLING



► EDP Code example: M4A 2.11/16 = 8073266826

► M4A Series No. 807326
► M4T Series No. 807304

▶ M4A Series No. 807326 ▶ M4T Series No. 807304						<table><tr><td>P</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>M</td><td></td><td></td><td></td><td>●</td><td>○</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>●</td><td>○</td><td></td><td></td><td>●</td></tr><tr><td>K</td><td>●</td><td>○</td><td></td><td>○</td><td>○</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>●</td><td>●</td><td>●</td><td>●</td></tr><tr><td>N</td><td></td><td></td><td></td><td>○</td><td>●</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>○</td><td>●</td><td></td><td></td><td></td></tr><tr><td>S</td><td></td><td></td><td></td><td></td><td>○</td><td>○</td><td></td><td></td><td></td><td>●</td><td>○</td><td></td><td></td><td></td><td></td><td>●</td><td>○</td></tr><tr><td>H</td><td></td><td></td><td></td><td></td><td></td><td>○</td><td>○</td><td></td><td>○</td><td>○</td><td></td><td></td><td></td><td></td><td></td><td>○</td><td>○</td></tr></table>												P																M				●	○								●	○			●	K	●	○		○	○									●	●	●	●	N				○	●								○	●				S					○	○				●	○					●	○	H						○	○		○	○						○	○
						P																																																																																																																					
						M				●	○								●	○			●																																																																																																				
						K	●	○		○	○									●	●	●	●																																																																																																				
						N				○	●								○	●																																																																																																							
S					○	○				●	○					●	○																																																																																																										
H						○	○		○	○						○	○																																																																																																										
HSS	SERIES	ORD Code	Size mm	Size Inch	f _n (mm/rev)	K10A	K10T	K20A	K20T	P40A	P40T	T15A	T15T	M4A	M4T	M48A	M48T																																																																																																										
	5	-6826	68.26	2.11/16	0.34 - 0.78									●	●																																																																																																												
		-6905	69.05	2.23/32										●	●																																																																																																												
		-6985	69.85	2.3/4											●	●																																																																																																											
		-7000	70.00												●	●																																																																																																											
		-7064	70.64	2.25/32											●	●																																																																																																											
		-7144	71.44	2.13/16											●	●																																																																																																											
		-7200	72.00												●	●																																																																																																											
		-7223	72.23	2.27/32											●	●																																																																																																											
		-7303	73.03	2.7/8											●	●																																																																																																											
		-7382	73.82	2.29/32											●	●																																																																																																											
		-7400	74.00												●	●																																																																																																											
		-7461	74.61	2.15/16											●	●																																																																																																											
		-7541	75.41	2.31/32											●	●																																																																																																											
		-7600	76.00												●	●																																																																																																											
		-7620	76.20	3											●	●																																																																																																											
	6	-7699	76.99	3.1/32	0.34 - 0.78										●	●																																																																																																											
		-7779	77.79	3.1/16											●	●																																																																																																											
		-7800	78.00												●	●																																																																																																											
		-7858	78.58	3.3/32											●	●																																																																																																											
		-7938	79.38	3.1/8											●	●																																																																																																											
		-8000	80.00												●	●																																																																																																											
		-8017	80.17	3.5/32											●	●																																																																																																											

ISO		P			M		K		N	S	H
MATERIAL		Non-alloy steel	Low alloy steel	High alloy steel	Ferritic / Martensitic Stainless steel	Austenitic Stainless steel	Grey Cast iron	Nodular Cast iron	Aluminium & Non-ferrous material	Heat Resistant and Super Alloys	Hardened steel
VDI GROUP		1-5	6-9	10-11	12-13	14	15-16	17-20	21-30	31-37	38
V _c (m/min)	K10A	-	-	-	-	-	79 - 111	125 - 137	-	-	-
	K10T	-	-	-	-	-	56 - 75	80 - 98	-	-	-
	K20A	-	-	-	50 - 62	46 - 52	79 - 111	125 - 137	244 - 366	24 - 30	-
	K20T	-	-	-	42 - 50	38 - 44	56 - 75	80 - 98	291 - 427	20 - 26	-
	P40A	84 - 125	64 - 102	50 - 67	-	-	-	-	-	-	47 - 62
	P40T	52 - 101	83 - 82	37 - 50	-	-	-	-	-	-	37 - 49
	T15A	-	41 - 58	26 - 34	-	-	41 - 52	-	-	11 - 12	21 - 35
	T15T	-	36 - 42	19 - 25	-	-	29 - 35	-	-	8 - 9	16 - 19
	M4A	66 - 84	41 - 75	-	29 - 34	27 - 29	-	58 - 75	92 - 187	-	-
	M4T	45 - 63	36 - 52	-	20 - 24	18 - 20	-	42 - 52	137 - 244	-	-
	M48A	-	41 - 58	26 - 34	-	-	41 - 52	-	-	11 - 12	21 - 35
	M48T	-	36 - 42	19 - 25	-	-	29 - 35	-	-	8 - 9	16 - 19

DRILLING



► EDP Code example:M4A 3.3/16 = 8073268096

► M4A Series No. 807326
► M4T Series No. 807304

						<table><tr><td>P</td><td></td><td></td><td></td><td></td><td>●</td><td>○</td><td></td><td>●</td><td></td><td>●</td><td></td><td>●</td><td></td><td>●</td><td></td><td>●</td></tr><tr><td>M</td><td></td><td></td><td></td><td>●</td><td>○</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>●</td><td>○</td><td></td><td>●</td></tr><tr><td>K</td><td>●</td><td>○</td><td>○</td><td>○</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>○</td><td>●</td><td>●</td><td>●</td></tr><tr><td>N</td><td></td><td></td><td>○</td><td>●</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>○</td><td>●</td><td></td><td></td></tr><tr><td>S</td><td></td><td></td><td>○</td><td>○</td><td></td><td></td><td></td><td></td><td></td><td>●</td><td>○</td><td></td><td></td><td></td><td></td><td>●</td><td>○</td></tr><tr><td>H</td><td></td><td></td><td></td><td></td><td></td><td>○</td><td>○</td><td>○</td><td>○</td><td></td><td></td><td></td><td></td><td></td><td></td><td>○</td><td>○</td></tr></table>												P					●	○		●		●		●		●		●	M				●	○									●	○		●	K	●	○	○	○										○	●	●	●	N			○	●										○	●			S			○	○						●	○					●	○	H						○	○	○	○							○	○
P					●	○		●		●		●		●		●																																																																																																												
M				●	○									●	○		●																																																																																																											
K	●	○	○	○										○	●	●	●																																																																																																											
N			○	●										○	●																																																																																																													
S			○	○						●	○					●	○																																																																																																											
H						○	○	○	○							○	○																																																																																																											
HSS	SERIES	ORD Code	Size mm	Size Inch	f _n (mm/rev)	K10A	K10T	K20A	K20T	P40A	P40T	T15A	T15T	M4A	M4T	M48A	M48T																																																																																																											
	6	-8096	80.96	3.3/16	0.34 - 0.78									●	●																																																																																																													
		-8176	81.76	3.7/32										●	●																																																																																																													
		-8200	82.00											●	●																																																																																																													
		-8255	82.55	3.1/4										●	●																																																																																																													
		-8334	83.34	3.9/32										●	●																																																																																																													
		-8400	84.00											●	●																																																																																																													
		-8414	84.14	3.5/16										●	●																																																																																																													
		-8493	84.93	3.11/32										●	●																																																																																																													
		-8573	85.73	3.3/8										●	●																																																																																																													
		-8600	86.00											●	●																																																																																																													
		-8652	86.52	3.13/32										●	●																																																																																																													
		-8731	87.31	3.7/16										●	●																																																																																																													
		-8800	88.00											●	●																																																																																																													
		-8811	88.11	3.15/32										●	●																																																																																																													
		-8890	88.90	3.1/2										●	●																																																																																																													
	7	-8969	89.69	3.17/32	0.34 - 0.78										●	●																																																																																																												
		-9000	90.00												●	●																																																																																																												
		-9049	90.49	3.9/16											●	●																																																																																																												
		-9128	91.28	3.19/32											●	●																																																																																																												
		-9200	92.00												●	●																																																																																																												
		-9208	92.08	3.5/8											●	●																																																																																																												
		-9287	92.87	3.21/32											●	●																																																																																																												

ISO		P			M		K		N	S	H
MATERIAL		Non-alloy steel	Low alloy steel	High alloy steel	Ferritic / Martensitic Stainless steel	Austenitic Stainless steel	Grey Cast iron	Nodular Cast iron	Aluminium & Non-ferrous material	Heat Resistant and Super Alloys	Hardened steel
VDI GROUP		1-5	6-9	10-11	12-13	14	15-16	17-20	21-30	31-37	38
V _c (m/min)	K10A	-	-	-	-	-	79 - 111	125 - 137	-	-	-
	K10T	-	-	-	-	-	56 - 75	80 - 98	-	-	-
	K20A	-	-	-	50 - 62	46 - 52	79 - 111	125 - 137	244 - 366	24 - 30	-
	K20T	-	-	-	42 - 50	38 - 44	56 - 75	80 - 98	291 - 427	20 - 26	-
	P40A	84 - 125	64 - 102	50 - 67	-	-	-	-	-	-	47 - 62
	P40T	52 - 101	83 - 82	37 - 50	-	-	-	-	-	-	37 - 49
	T15A	-	41 - 58	26 - 34	-	-	41 - 52	-	-	11 - 12	21 - 35
	T15T	-	36 - 42	19 - 25	-	-	29 - 35	-	-	8 - 9	16 - 19
	M4A	66 - 84	41 - 75	-	29 - 34	27 - 29	-	58 - 75	92 - 187	-	-
	M4T	45 - 63	36 - 52	-	20 - 24	18 - 20	-	42 - 52	137 - 244	-	-
	M48A	-	41 - 58	26 - 34	-	-	41 - 52	-	-	11 - 12	21 - 35
	M48T	-	36 - 42	19 - 25	-	-	29 - 35	-	-	8 - 9	16 - 19

P						●	○	●	●	●	●	●	●	●
M			●	○					●	○				
K	●	○		○	○				●	○	●	●	●	●
N			○	●					○	●				
S			○	○			●	○	○			●	○	○
H						○	○	○	○			○	○	

[illegible]182 Europa Tool Co.,Ltd

P						●	○	●	●	●	●	●	●
M				●	○				●	○			
K	●	○		○	○				●	○	●	●	●
N				○	●				○	●			
S				○	○			●	○	○		●	○
H						○	○	○	○			○	○

HSS	SERIES	ORD Code	Size mm	Size Inch	f _n (mm/rev)	K10A	K10T	K20A	K20T	P40A	P40T	T15A	T15T	M4A	M4T	M48A	M48T		
	8	-10800	108.00		0.34 - 0.78									●	●				
		-10954	109.54	4.5/16												●	●		
		-11000	110.00													●	●		
		-11113	111.13	4.3/8												●	●		
		-11200	112.00													●	●		
		-11271	112.71	4.7/16												●	●		
		-11400	114.00													●	●		
		-11430	114.30	4.1/2												●	●		

Europa Tool Co.,Ltd
183